

TETRA Interoperability Certificate

Hytera Mobilfunk, ACCESSNET-T IP , SwMI – Sepura, SRG3900, Terminal

Flensburg, September 2017

| | | | |
|--------------------------------------|----------|--|-----------------|
| Latest Certified SwMI SW Release: | PV 9.1.3 | Latest Certified Terminal SW Release: | 1746 012 03577 |
| Latest Certified SwMI HW Release: | PV 9 | Latest Certified Terminal HW Release: | MSUTW201T2COG00 |

ISCTI (Istituto Superiore delle Comunicazioni e delle Tecnologie dell'Informazione) certifies, that the Hytera Mobilfunk, ACCESSNET-T IP , SwMI and the Sepura, SRG3900, terminal have been subject to interoperability testing for the “certified” features listed on second page of this certificate, in accordance with the TETRA Interoperability Profiles, TIP compliance Test Plan and related TETRA interoperability requirement tables.

The table lists all the available TETRA interoperability profiles, and summarizes the main functionalities of every profile according to the TETRA interoperability requirement tables.

A feature is “Certified” when it has been successfully tested during the last test session with one of the testing method described in the TETRA process document part 1 (TPD001-01).

A breakdown into the feature details is given in the Feature Compliance Overview section of this certificate.


This certificate has been issued following the fully witnessed single test session between Hytera Mobilfunk and Sepura on September 2017. Detailed test results are listed in the Test Report associated to this Certificate. Details and explanation about the procedure used to provide verdicts are in the TIC process TPD001-01.

IOP test engineer



Franco Pangallo

Head of the Procedure



Ivano Luciani

Radio Office Manager



Giuseppe Pierri

ISCTI - V.le America 201, 00144 Rome, Italy
Ph.: +39 06 5444 2135, Fax: +39 06 5410904
e-mail: tetra_ctc.iscom@mise.gov.it,
Web: www.mise.gov.it

Date of issue:
17 October 2017

v1

Certified features

| Tetra Association TTR001-01:Core | |
|---|-----------|
| Registration | Certified |
| Group Management | Certified |
| Group call | Certified |
| Individual call | Certified |
| Status messages | Certified |
| Pre-emptive Priority Call | Certified |
| Emergency Call | Certified |
| Cell Re-selection | Certified |
| PSTN interconnect | Certified |
| MS-ISDN Numbering | - |
| In Call Signalling | Certified |
| Subscriber Class Procedures | Certified |
| Common Secondary Control Channels | Certified |
| BS Fallback Operation | Certified |
| Energy Economy Mode | - |
| Transmit Inhibit | Certified |
| Mixed band operation | Certified |
| Tetra Association TTR001-02:SDS | |
| SDS Type 1, 2 or 3 | - |
| SDS-TL | Certified |
| Store and Forward | - |
| Multipart SDS | - |
| Tetra Association TTR001-03:DGNA | |
| Support for individually addressed DGNA | Certified |
| Support for group addressed DGNA | - |

| | |
|--|--------------------|
| Tolerance of unsupported DGNA functions | - |
| Tetra Association TTR001-04:Auth | |
| SwMI Initiated (non-mutual) Authentication | Certified |
| SwMI Initiated Authentication made Mutual by MS | Certified |
| TEI Query | - |
| Tetra Association TTR001-05:PD | |
| Context Management | Certified |
| Single Slot Packet Data | Certified |
| Multi Slot Packet Data | Certified |
| TEDS | - |
| Mixed band operation | - |
| Tetra Association TTR001-09:AL | |
| Ambience Listening | Certified |
| Interaction with Transmit Inhibit | Certified |
| Tetra Association TTR001-10:E2EE | |
| E2EE Voice Call | Certified |
| Tetra Association TTR001-11:AIE | |
| Security Class 2 Air Interface Encryption | Certified (Note 1) |
| Security Class 3 Air Interface Encryption | Certified |
| Security Class 3G Air Interface Encryption | - |
| Management of CMG and GSKO | - |
| Key Status demand | - |
| Change of Security Class for Fallback operation | - |
| Change of Security Class (other than for Fallback operation) | - |
| Key Management for Secure Direct Mode Operation | - |
| Tetra Association TTR001-12:SI | |
| MS initiated Service Interaction | Certified |
| SwMI initiated Service Interaction | Certified |
| Call Waiting | - |

| Tetra Association TTR001-13:ED | |
|---------------------------------------|-----------|
| Enable and temporary disable of an MS | Certified |
| Permanent disable of an MS | Certified |
| Tetra Association TTR001-14:TKD | |
| Delivery of Authentication Data | Certified |
| Delivery of SCK | Certified |
| Delivery method | Certified |
| Tetra Association TTR001-19:LIP | |
| Location Information Protocol | Certified |
| Tetra Association TTR001-20:CF | |
| Call Forwarding Unconditional | Certified |
| Call Forwarding Conditional | Certified |
| Call Forwarding Information Displayed | - |
| Management of Call Forwarding | - |

Note 1: a Tic-Rt declaration was changed after the start of the session. Due to a human error the original declaration was filled out wrongly. Please refer to the Test Report for details.

Feature Compliance Overview

The first pages of this certificate provide an indication about the main interoperable TETRA features for each TIP specification (as described in the TIC-RT). The main interoperable TETRA features' results depend on a set of sub-features, the verdicts associated to each sub-feature are directly derived from the analysis of the performed test cases.

The results associated to each feature and sub-feature are shown in the "Feature Compliance Report" table below. The main features are indicated with blue background and the associated sub-features (or second level features) have a white background.

The outcome assigned to a feature as shown on page 2, is derived by the Feature Compliance Report tables.

| Outcome | Definition |
|------------------|---|
| Certified | All required tests have been performed and passed |
| Partial | Not all the required tests have been performed but none have failed |
| - | Feature cannot be certified e.g. it is not supported by at least one product, no tests were performed, or some tests were performed but at least one failed |

The outcome is derived from the verdict assigned to a sub feature which is the result of an analysis of the test case results listed in the Test Report. The verdict assigned to each sub-feature is derived from one or several test case results or test steps result, the TETRA Interoperability requirement tables (TIC-RTs) indicate the link between sub-features and test cases for the certified set of equipment capabilities (see Test Report).

| Verdict | Definition |
|-------------------|---|
| Passed | All mandated tests or steps of tests linked to this functionality (as per TIC-RT indication) are compliant with the TIP specification relevant to this feature or sub-feature |
| Incomplete | Not all Mandated tests (as per TIC-RT indication) have been executed |
| Failed | At least one of mandated test or steps of tests linked to this functionality failed to match the TIP specification relevant to this feature or sub-feature |

The verdict associated to the feature or sub-feature gives also indication about the method used to test that feature or sub-feature. The allowed testing Methods are listed in the table below, a complete description of the procedures and constraints associated to each of them can be found in the "TPD001-01 TETRA Interoperability Certification Process Description" document.

| Testing Method | Description |
|---------------------------|--|
| Complete | All mandated tests associated to the feature or sub-feature have been executed |
| Spot | Only a selection of the mandatory test cases associated to the feature or sub-feature has been executed during the test session. These tests are a subset of the tests performed on an equivalent software which has been "completely" tested against the same functionality on a different equipment, see manufacturer declaration in the associated Test Report |
| Regression | Only a selection of the mandatory test cases associated to the feature or sub-feature has been executed during the test session. These tests are a subset of the tests performed on a previous version of the same software which has been "completely" tested in a previous test session against the same functionality, see manufacturer definition in the associated Test Report |
| Regression on spot | The regression method (see the previous item) has been applied at this session on the verdicts from the referenced (previous) session where the spot testing method (see above) had been applied. |
| Witnessed | The TIP heading lines in the Feature Compliance Report indicate whether each TIP is partially or fully witnessed by the Certification Body. Additionally, for a partially-witnessed TIP, the number of witnessed test cases that passed is shown for each the feature and sub-feature. There may have been some un-witnessed passed tests and they will have been found to be successful based on the log file evaluation |

Depending on equipment capabilities declared by the manufacturer, some features or sub features cannot be tested. The following table describes meaning of the used abbreviation:

| Indication | Definition |
|------------|------------|
|------------|------------|

| | |
|----------------------|---|
| Not supported | The SwMI and/or MS do not support the minimum features required to verify these items |
|----------------------|---|

ISCTI has made every effort to ensure that every result has been correctly evaluated in accordance with the relevant TIPs, Test Plans and TIC-RTs. ISCTI has no liability for the test results, or towards the manufacturers.

The table on the following page lists HW and SW releases of SwMI and Terminal under test in the last four test sessions and the used TIP specifications, Test Plans and TIC-RTs.

This Certificate and Certificates from previous test sessions are available on the [TETRA + Critical Communications Association](https://tandcca.com/interoperability/interoperability-certificates-and-test-reports/) web site (https://tandcca.com/interoperability/interoperability-certificates-and-test-reports/).

The feature results are shown in the tables below.

Information on equipment under test and document references

| | | | | |
|---|--|--|--|--|
| Test Session Date/Place | Hytera Mobilfunk, Flensburg, September 2017 | | | |
| SwMI Type | ACCESSNET-T IP | | | |
| SwMI HW Release | PV 9 | | | |
| SwMI SW Release | PV 9.1.3 | | | |
| Terminal Type | SRG3900 | | | |
| Terminal HW Release | MSUTW201T2C0G00 | | | |
| Terminal SW Release | 1746 012 03577 | | | |
| TIP Specs and TIP Compliance Test Plans | | | | |

| | | | | |
|-------------|---|--|--|--|
| Core | TTR001-01 v6.2.2 IOP001-01 v3.2.0 TIC-RT001-01 v271 | | | |
| SDS | TTR001-02 v2.1.3 IOP001-02 v2.1.0 TIC-RT001-02 v222 | | | |
| DGNA | TTR001-03 v2.0.0 IOP001-03 v2.0.1 TIC-RT001-03 v228 | | | |
| Auth | TTR001-04 v3.0.0 IOP001-04 v2.0.0 TIC-RT001-04 v230 | | | |
| PD | TTR001-05 v4.1.0 IOP001-05 v4.1.0 TIC-RT001-05 v405 | | | |
| AL | TTR001-09 v2.0.0 IOP001-09 v1.1.0 TIC-RT001-09 v129 | | | |
| E2EE | TTR001-10 v2.1.0 IOP001-10 v1.1.4 TIC-RT001-10 v128 | | | |
| AIE | TTR001-11 v3.0.3 IOP001-11 v3.1.0 TIC-RT001-11 v331 | | | |
| SI | TTR001-12 v1.1.0 IOP001-12 v1.0.0 TIC-RT001-12 v133 | | | |
| ED | TTR001-13 v2.1.0 IOP001-13 v1.0.0 TIC-RT001-13 v151 | | | |
| TKD | TTR001-14 v1.0.3 IOP001-14 v1.0.0 TIC-RT001-14 v122 | | | |
| LIP | TTR001-19 v1.1.0 IOP001-19 v1.1.0 TIC-RT001-19 v114 | | | |

| | | | | |
|----|---|--|--|--|
| CF | TTR001-20 v1.0.1 IOP001-20 v1.0.0 TIC-RT001-20 v114 | | | |
|----|---|--|--|--|

Feature compliance report

| Test Session | Hytera Mobilfunk, September 2017 Flensburg | | | |
|---|---|--|--|--|
| Core - Fully Witnessed Testing | | | | |
| Registration | PASSED Complete 7_pass_of_7 | | | |
| Initial registration | PASSED Complete 2_pass_of_2 | | | |
| SwMI initiated location updating | PASSED Complete 2_pass_of_2 | | | |
| LA timer based Periodic location updating | PASSED Complete 2_pass_of_2 | | | |
| De-registration | PASSED Complete 1_pass_of_1 | | | |
| Group Management | PASSED Complete 12_pass_of_12 | | | |
| Single group attachment | PASSED Complete 6_pass_of_6 | | | |
| Multiple group attachment | PASSED Complete 5_pass_of_5 | | | |
| MS initiated group detachment | PASSED Complete 1_pass_of_1 | | | |

| | | | | |
|---|----------------------------------|--|--|--|
| SwMI initiated group management | PASSED Complete 1_pass_of_1 | | | |
| Group call | PASSED Complete 11_pass_of_11 | | | |
| Normal group call | PASSED Complete 4_pass_of_4 | | | |
| Late entry | PASSED Complete 1_pass_of_1 | | | |
| Priority Group scanning | PASSED Complete 3_pass_of_3 | | | |
| Call setup modifications | PASSED Complete 1_pass_of_1 | | | |
| Resource Queuing based on Call Priority | PASSED Complete 1_pass_of_1 | | | |
| Broadcast Call | PASSED Complete 1_pass_of_1 | | | |
| Limited coverage notification | Not Supported | | | |
| Individual call | PASSED Complete 10_pass_of_10 | | | |
| Simplex individual call | PASSED Complete 4_pass_of_4 | | | |
| Duplex individual call | PASSED Complete 2_pass_of_2 | | | |
| Call setup modifications | PASSED Complete 2_pass_of_2 | | | |
| Resource Queuing based on Call Priority | PASSED Complete 2_pass_of_2 | | | |
| Indication of imminent call disconnection | Not Supported | | | |
| Status messages | PASSED Complete 4_pass_of_4 | | | |
| Individual addressed Status transfer | PASSED Complete 1_pass_of_1 | | | |
| Group addressed Status transfer | PASSED Complete | | | |

| | | | | |
|--|----------------------------------|--|--|--|
| | 3_pass_of_3 | | | |
| Pre-emptive Priority Call | PASSED Complete 7_pass_of_7 | | | |
| Pre-emption of Resources | PASSED Complete 2_pass_of_2 | | | |
| Pre-emption of Busy Users | PASSED Complete 5_pass_of_5 | | | |
| Emergency Call | PASSED Complete 4_pass_of_4 | | | |
| Pre-emption of Resources | PASSED Complete 2_pass_of_2 | | | |
| Pre-emption of Busy Users | PASSED Complete 1_pass_of_1 | | | |
| Call setup modifications | PASSED Complete 1_pass_of_1 | | | |
| Call disconnection by non-call owner | Not Supported | | | |
| Cell Re-selection | PASSED Complete 16_pass_of_16 | | | |
| Undeclared | PASSED Complete 1_pass_of_1 | | | |
| Unannounced | PASSED Complete 3_pass_of_3 | | | |
| Announced - with Call Restoration | PASSED Complete 12_pass_of_12 | | | |
| Announced - without Call Restoration | Not Supported | | | |
| Expedited | Not Supported | | | |
| Graceful Service Degradation Mode (GSDM) | Not Supported | | | |
| PSTN interconnect | PASSED Complete 6_pass_of_6 | | | |
| TETRA Originated Call | PASSED Complete 2_pass_of_2 | | | |
| PSTN Originated Call | PASSED Complete 1_pass_of_1 | | | |

| | | | | |
|--|----------------------------------|--|--|--|
| DTMF over-dial | PASSED Complete 1_pass_of_1 | | | |
| Emergency Telephone Calls | PASSED Complete 2_pass_of_2 | | | |
| MS-ISDN Numbering | | | | |
| MS ISDN - Voice Call | Not Supported | | | |
| MS-ISDN Status | Not Supported | | | |
| In Call Signalling | PASSED Complete 6_pass_of_6 | | | |
| Slow Signalling on Traffic Channel (SACCH) | PASSED Complete 2_pass_of_2 | | | |
| Fast Signalling on Traffic Channel (FACCH) | PASSED Complete 4_pass_of_4 | | | |
| Subscriber Class Procedures | PASSED Complete 9_pass_of_9 | | | |
| Cell Selection based on Subscriber Class | PASSED Complete 3_pass_of_3 | | | |
| Subscriber Class Delivery during Location Update | PASSED Complete 3_pass_of_3 | | | |
| Use of Subscriber Class Preference Levels | PASSED Complete 3_pass_of_3 | | | |
| Common Secondary Control Channels | PASSED Complete 6_pass_of_6 | | | |
| One C-SCCH per cell | PASSED Complete 4_pass_of_4 | | | |
| Two C-SCCH per cell | PASSED Complete 2_pass_of_2 | | | |
| Three C-SCCH per cell | PASSED Complete 2_pass_of_2 | | | |
| BS Fallback Operation | PASSED Complete 13_pass_of_13 | | | |
| Switch to/from BS Fallback Operation | PASSED Complete 2_pass_of_2 | | | |

| | | | | |
|--|----------------------------------|--|--|--|
| Roaming to avoid a cell in BS Fallback Operation | PASSED Complete 2_pass_of_2 | | | |
| Services with BS Fallback Operation | PASSED Complete 8_pass_of_8 | | | |
| Ignore a cell in Fallback Operation | PASSED Complete 1_pass_of_1 | | | |
| User selectable Fallback behaviour | Not Supported | | | |
| Energy Economy Mode | | | | |
| Energy Economy Mode Operation | Not Supported | | | |
| Transmit Inhibit | PASSED Complete 5_pass_of_5 | | | |
| TXI Activation & De-Activation | PASSED Complete 4_pass_of_4 | | | |
| TXI Activation & De-Activation with TxI Status available to the Dispatcher | Not Supported | | | |
| Receipt of group addressed service during TXI | PASSED Complete 1_pass_of_1 | | | |
| Mixed band operation | | | | |
| Mixed band operation, inter-cell | Not Supported | | | |
| Mixed band operation, intra-cell | Not Supported | | | |
| Mixed band operation, Full | Not Supported | | | |
| SDS - Fully Witnessed Testing | | | | |
| SDS Type 1, 2 or 3 | | | | |
| SDS Type 1 | Not Supported | | | |
| SDS Type 2 | Not Supported | | | |
| SDS Type 3 | Not Supported | | | |
| SDS-TL | PASSED Complete 15_pass_of_15 | | | |
| Individually Addressed | PASSED Complete 2_pass_of_2 | | | |
| Group Addressed | PASSED Complete 3_pass_of_3 | | | |
| Using MS-ISDN dialling | Not Supported | | | |

| | | | | |
|--|----------------------------------|--|--|--|
| SDS Reception | PASSED Complete 8_pass_of_8 | | | |
| Using UCS2 coding scheme | PASSED Complete 2_pass_of_2 | | | |
| Using 7-bit coding scheme | PASSED Complete 2_pass_of_2 | | | |
| Using 8-bit Latin 1 coding scheme | PASSED Complete 2_pass_of_2 | | | |
| Using 8-bit Latin/Cyrillic coding scheme | PASSED Complete 2_pass_of_2 | | | |
| Using 8-bit Latin 9 coding scheme | PASSED Complete 2_pass_of_2 | | | |
| Store and Forward | | | | |
| Individually Addressed | Not Supported | | | |
| Group Addressed | Not Supported | | | |
| Multipart SDS | | | | |
| Multipart SDS | Not Supported | | | |
| DGNA - Fully Witnessed Testing | | | | |
| Support for individually addressed DGNA | PASSED Complete 12_pass_of_12 | | | |
| Support for individually addressed DGNA assignment without attachment | PASSED Complete 3_pass_of_3 | | | |
| Support for individually addressed DGNA assignment with attachment as selected group | PASSED Complete 3_pass_of_3 | | | |
| Support for individually addressed DGNA assignment with attachment as scanned group | PASSED Complete 4_pass_of_4 | | | |
| Support for individually addressed DGNA assignment with rejected attachment | Not Supported | | | |
| Support for individually addressed assignment for pre-programmed group | PASSED Complete 5_pass_of_5 | | | |
| Support for group addressed DGNA | | | | |

| | | | | |
|--|----------------------------------|--|--|--|
| Support for group addressed DGNA assignment | Not Supported | | | |
| Management of 'group assignment lifetime' | Not Supported | | | |
| Support for group addressed DGNA deassignment | Not Supported | | | |
| Tolerance of unsupported DGNA functions | | | | |
| MS tolerance of unsupported individual addressed DGNA signalling | Not Supported | | | |
| MS tolerance of unsupported group addressed DGNA signalling | Not Supported | | | |
| Auth - Fully Witnessed Testing | | | | |
| SwMI Initiated (non-mutual) Authentication | PASSED Complete 3_pass_of_3 | | | |
| Attach with authentication | PASSED Complete 1_pass_of_1 | | | |
| Roaming with authentication | PASSED Complete 1_pass_of_1 | | | |
| SwMI rejects MS during authentication | PASSED Complete 1_pass_of_1 | | | |
| MS rejects SwMI during authentication | Not Supported | | | |
| SwMI Initiated Authentication made Mutual by MS | PASSED Complete 2_pass_of_2 | | | |
| Attach with authentication | PASSED Complete 1_pass_of_1 | | | |
| Roaming with authentication | PASSED Complete 1_pass_of_1 | | | |
| TEI Query | | | | |
| TEI Query Operation | Not Supported | | | |
| PD - Fully Witnessed Testing | | | | |
| Context Management | PASSED Complete 12_pass_of_12 | | | |
| Context Activation | PASSED Complete 8_pass_of_8 | | | |

| | | | | |
|--|----------------------------------|--|--|--|
| User authentication | PASSED Complete 4_pass_of_4 | | | |
| Single Slot Packet Data | PASSED Complete 10_pass_of_10 | | | |
| Data Transfer | PASSED Complete 6_pass_of_6 | | | |
| Cell re-selection | PASSED Complete 3_pass_of_3 | | | |
| Packet Data Channel sharing | PASSED Complete 1_pass_of_1 | | | |
| Multi Slot Packet Data | PASSED Complete 2_pass_of_2 | | | |
| Data Transfer | PASSED Complete 2_pass_of_2 | | | |
| TEDS | | | | |
| TEDS with Context Activation | Not Supported | | | |
| TEDS Data Transmission, using LLC Optimisation | Not Supported | | | |
| TEDS Cell Reselection, using LLC Optimisation | Not Supported | | | |
| Mixed band operation | | | | |
| Mixed band operation, inter-cell | Not Supported | | | |
| Mixed band operation, intra-cell | Not Supported | | | |
| Mixed band operation, Full | Not Supported | | | |
| AL - Fully Witnessed Testing | | | | |
| Ambience Listening | PASSED Complete 5_pass_of_5 | | | |
| SS-AL Call Setup | PASSED Complete 2_pass_of_2 | | | |
| MS initiated SS-AL disconnection | PASSED Complete 3_pass_of_3 | | | |
| No Indication to affected user | PASSED Complete 5_pass_of_5 | | | |
| Interaction with Transmit Inhibit | PASSED Complete | | | |

| | | | | |
|--|----------------------------------|--|--|--|
| | 2_pass_of_2 | | | |
| AL can override TxI | PASSED Complete 1_pass_of_1 | | | |
| AL cannot override TxI | PASSED Complete 1_pass_of_1 | | | |
| E2EE - Fully Witnessed Testing | | | | |
| E2EE Voice Call | PASSED Complete 6_pass_of_6 | | | |
| Individual (P2P) call | PASSED Complete 4_pass_of_4 | | | |
| Group (P2MP) call | PASSED Complete 2_pass_of_2 | | | |
| Clear Voice Override (CVO): Acceptance | Not Supported | | | |
| Clear Voice Override (CVO): User Initiated | Not Supported | | | |
| Clear Voice Override (CVO): Automatic | Not Supported | | | |
| AIE - Fully Witnessed Testing | | | | |
| Security Class 2 Air Interface Encryption | PASSED Complete 14_pass_of_14 | | | |
| Location Updating and AI Signalling Protection | PASSED Complete 3_pass_of_3 | | | |
| TM-SCK provisioning during location updating | Not Supported | | | |
| Communications between parties using encryption | PASSED Complete 2_pass_of_2 | | | |
| Communications between clear and encrypted parties | PASSED Complete 3_pass_of_3 | | | |
| Communications between encrypted parties on a channel designated to operate in clear | PASSED Complete 2_pass_of_2 | | | |
| OTAR of TM-SCK | Not Supported | | | |
| Change of TM-SCK | PASSED Complete 2_pass_of_2 | | | |
| Packet Data with Class 2 Air Interface Encryption | PASSED Complete | | | |

| | | | | |
|--|----------------------------------|--|--|--|
| | 2_pass_of_2 | | | |
| Tolerance of SwMI not supporting SCK-OTAR | Not Supported | | | |
| Security Class 3 Air Interface Encryption | PASSED Complete 12_pass_of_12 | | | |
| Clear Location Updating and AI Signalling Protection | PASSED Complete 3_pass_of_3 | | | |
| Encrypted Location Updating and AI Signalling Protection | Not Supported | | | |
| DCK Forwarding at MS request | Not Supported | | | |
| DCK Forwarding by SwMI (without MS request) | Not Supported | | | |
| DCK Retrieval | Not Supported | | | |
| CCK provisioning during location updating | PASSED Complete 3_pass_of_3 | | | |
| Communications between parties using encryption | PASSED Complete 2_pass_of_2 | | | |
| Communications between clear and encrypted parties | PASSED Complete 3_pass_of_3 | | | |
| Communications between encrypted parties on a channel designated to operate in clear | PASSED Complete 2_pass_of_2 | | | |
| OTAR of CCK | Not Supported | | | |
| Change of CCK | Not Supported | | | |
| Packet Data with Class 3 Air Interface Encryption | PASSED Complete 2_pass_of_2 | | | |
| Security Class 3G Air Interface Encryption | | | | |
| GCK Key Association setting | Not Supported | | | |
| Communications between parties using encryption | Not Supported | | | |
| Communications between clear and encrypted parties | Not Supported | | | |
| OTAR of GCK | Not Supported | | | |
| Change of GCK | Not Supported | | | |
| Management of CMG and GSKO | | | | |

| | | | | |
|---|--------------------------------|--|--|--|
| OTAR and change of CMG and GSKO | Not Supported | | | |
| Key Status demand | | | | |
| SCK Key Status demand | Not Supported | | | |
| GCK Key Status demand | Not Supported | | | |
| GSKO Key Status demand | Not Supported | | | |
| Change of Security Class for Fallback operation | | | | |
| Seamless change to Security Class 2 for BS Fallback operation | Not Supported | | | |
| Non-seamless change to Security Class 2 for BS Fallback operation | Not Supported | | | |
| Provisioning of TM-SCK for fallback to Security Class 2 operation | Not Supported | | | |
| Change to Security Class 1 for BS Fallback operation | Not Supported | | | |
| Change of Security Class (other than for Fallback operation) | | | | |
| Change between Security Class 3 and Security Class 3G | Not Supported | | | |
| Change between Security Class 2 and Security Class 3 | Not Supported | | | |
| Change from Security Class 3G to Security Class 2 | Not Supported | | | |
| Key Management for Secure Direct Mode Operation | | | | |
| OTAR of DM-SCK | Not Supported | | | |
| Change of DM-SCK | Not Supported | | | |
| SI - Fully Witnessed Testing | | | | |
| MS initiated Service Interaction | PASSED Complete 7_pass_of_7 | | | |
| MS initiated Circuit Mode Call during another Circuit Mode Call | PASSED Complete 5_pass_of_5 | | | |
| MS initiated Circuit Mode Call during Packet Mode Transfer | PASSED Complete 2_pass_of_2 | | | |
| MS initiated Packet Mode Transfer during Circuit Mode Call | Not Supported | | | |
| SwMI initiated Service Interaction | PASSED Complete | | | |

| | | | | |
|---|----------------------------------|--|--|--|
| | 10_pass_of_10 | | | |
| SwMI initiated Circuit Mode Call during another Circuit Mode Call | PASSED Complete 8_pass_of_8 | | | |
| SwMI initiated Circuit Mode Call during Packet Mode Transfer | PASSED Complete 2_pass_of_2 | | | |
| SwMI initiated Packet Mode Transfer during Circuit Mode Call | Not Supported | | | |
| Call Waiting | | | | |
| Call Waiting in Individual Call | Not Supported | | | |
| Call Waiting in Group Call | Not Supported | | | |
| ED - Fully Witnessed Testing | | | | |
| Enable and temporary disable of an MS | PASSED Complete 20_pass_of_20 | | | |
| Enable and temporary disable of an MS without authentication | PASSED Complete 6_pass_of_6 | | | |
| Enable and temporary disable of an MS with authentication | PASSED Complete 6_pass_of_6 | | | |
| Registration of a temporary disabled MS | PASSED Complete 2_pass_of_2 | | | |
| Rejection of applicable invalid enable/disable requests | PASSED Complete 4_pass_of_4 | | | |
| Removable SIMs do not affect the subscriber or equipment that has been enabled/disabled | Not Supported | | | |
| Disabling of an MS during a call or while on the PDCH | PASSED Complete 2_pass_of_2 | | | |
| Permanent disable of an MS | PASSED Complete 4_pass_of_4 | | | |
| Permanent disable of an MS with authentication | PASSED Complete 3_pass_of_3 | | | |
| Permanently Disabled MS cannot send air interface signalling | PASSED Complete 1_pass_of_1 | | | |
| TKD - Fully Witnessed Testing | | | | |

| | | | | |
|---|----------------------------------|--|--|--|
| Delivery of Authentication Data | PASSED Complete 2_pass_of_2 | | | |
| Authentication Key Delivery | PASSED Complete 1_pass_of_1 | | | |
| ITSI Delivery | PASSED Complete 1_pass_of_1 | | | |
| Delivery of SCK | PASSED Complete 1_pass_of_1 | | | |
| SCK Delivery to SCK delivery | Not Supported | | | |
| SCK Delivery to SwMI | PASSED Complete 1_pass_of_1 | | | |
| SCK Delivery to SCK loading | Not Supported | | | |
| Delivery method | PASSED Complete 3_pass_of_3 | | | |
| Plain text on physical media | PASSED Complete 3_pass_of_3 | | | |
| Encrypted text on physical media | Not Supported | | | |
| Electronic transfer | Not Supported | | | |
| LIP - Fully Witnessed Testing | | | | |
| Location Information Protocol | PASSED Complete 12_pass_of_12 | | | |
| LIP over SDS | PASSED Complete 6_pass_of_6 | | | |
| LIP over Packet Data | Not Supported | | | |
| Time based reporting | PASSED Complete 2_pass_of_2 | | | |
| Distance based reporting - NOT TESTABLE | Not Supported | | | |
| Reporting using Short reports | PASSED Complete 2_pass_of_2 | | | |
| Reporting using Long reports | PASSED Complete 2_pass_of_2 | | | |
| Reporting Enable & Disable | PASSED Complete 1_pass_of_1 | | | |

| | | | | |
|--|--------------------------------|--|--|--|
| User control of Reporting | PASSED Complete 1_pass_of_1 | | | |
| Temporary reporting control | Not Supported | | | |
| Trigger modification | Not Supported | | | |
| Control of Basic Location Parameters | Not Supported | | | |
| Immediate Location Reporting | PASSED Complete 1_pass_of_1 | | | |
| Reporting Lifetimes | Not Supported | | | |
| Error Reporting using Long Reports | PASSED Complete 1_pass_of_1 | | | |
| Error Reporting using Short Reports | PASSED Complete 1_pass_of_1 | | | |
| Positioning on Individual Call Setup | Not Supported | | | |
| CF - Fully Witnessed Testing | | | | |
| Call Forwarding Unconditional | PASSED Complete 3_pass_of_3 | | | |
| Call Forwarding Unconditional Individual Call | PASSED Complete 1_pass_of_1 | | | |
| Call Forwarding Unconditional SDS | PASSED Complete 1_pass_of_1 | | | |
| Call Forwarding Unconditional Status | PASSED Complete 1_pass_of_1 | | | |
| Call Forwarding Conditional | PASSED Complete 3_pass_of_3 | | | |
| Call Forwarding Conditional Individual Call | PASSED Complete 3_pass_of_3 | | | |
| Call Forwarding Information Displayed | | | | |
| Call Forwarding Information Displayed | Not Supported | | | |
| Management of Call Forwarding | | | | |
| Change of Call Forwarding Activation Status by Served User | Not Supported | | | |
| Setting of Call Forwarding Parameters by Served User | Not Supported | | | |