

TETRA Interoperability Certificate

Motorola, Dimetra IP R7.1, SwMI – Motorola, MTP3150, Terminal

Krakow, December 2013

Latest Certified SwMI SW Release:	7.1	Latest Certified Terminal SW Release:	MR10.7
Latest Certified SwMI HW Release:	Dimetra IP R7.1	Latest Certified Terminal HW Release:	PT912OHE

ISCTI (Istituto Superiore delle Comunicazioni e delle Tecnologie dell'Informazione) certifies, that the Motorola, Dimetra IP R7.1, SwMI and the Motorola, MTP3150, terminal have been subject to interoperability testing for the “certified” features listed on second page of this certificate, in accordance with the TETRA Interoperability Profiles, TIP compliance Test Plan and related TETRA interoperability requirement tables.

The table lists all the available TETRA interoperability profiles, and summarizes the main functionalities of every profile according to the TETRA interoperability requirement tables.

A feature is “Certified” when it has been successfully tested during the last test session with one of the testing method described in the TETRA process document part 1 (TPD001-01).

A breakdown into the feature details is given in the Feature Compliance Overview section of this certificate.

This certificate has been issued following a fully witnessed single test session between Motorola and Motorola on December 2013. Detailed test results are listed in the Test Report associated to this Certificate. Details and explanation about the procedure used to provide verdicts are in the TIC process TPD001-01.

IOP test engineer


Roberto Lo Sterzo

Radio Office Manager

Giuseppe Pierri


ISCTI - V.le America 201, 00144 Rome, Italy
Ph.: +39 06 5444 2135, Fax: +39 06 5410904
e-mail: tetra_ctc.iscom@mise.gov.it,
Web: www.mise.gov.it

Date of issue
20 January 2014
v 1

Certified features

Tetra Association TTR001-01:Core	
Registration	Certified
Group Management	Certified
Group call	Certified
Individual call	Certified
Status messages	Certified
Pre-emptive Priority Call	Certified
Emergency Call	Certified
Cell Re-selection	Certified
PSTN interconnect	Certified
MS-ISDN Numbering	-
In Call Signalling	Certified
Subscriber Class Procedures	Partial
Common Secondary Control Channels	Certified
BS Fallback Operation	Certified
Energy Economy Mode	Certified
Transmit Inhibit	Certified
Mixed band operation	Certified
Tetra Association TTR001-02:SDS	
SDS Type 1, 2 or 3	-
SDS-TL	Certified
Store and Forward	Certified
Tetra Association TTR001-03:DGNA	
Support for individually addressed DGNA	Certified
Support for group addressed DGNA	Partial
Tolerance of unsupported DGNA functions	-

Tetra Association TTR001-04:Auth	
SwMI Initiated (non-mutual) Authentication	Certified
SwMI Initiated Authentication made Mutual by MS	Certified
TEI Query	-
Tetra Association TTR001-05:PD	
Context Management	Certified
Single Slot Packet Data	Certified
Multi Slot Packet Data	Certified
TEDS	-
Mixed band operation	Certified
Tetra Association TTR001-09:AL	
Ambience Listening	Certified
Interaction with Transmit Inhibit	Certified
Tetra Association TTR001-11:AIE	
Security Class 2 Air Interface Encryption	-
Security Class 3 Air Interface Encryption	Partial
Security Class 3G Air Interface Encryption	Partial
Change of CMG and GSKO	Certified
Key Status demand	Certified
Change of Security Class for Fallback operation	Certified
Change of Security Class (other than for Fallback operation)	Certified
Key Management for Secure Direct Mode Operation	Certified
Tetra Association TTR001-12:SI	
MS initiated Service Interaction	Certified
SwMI initiated Service Interaction	Certified
Call Waiting	-

Tetra Association TTR001-13:ED	
Enable and temporary disable of an MS	Certified
Permanent disable of an MS	Certified

Feature Compliance Overview

The first pages of this certificate provide an indication about the main interoperable TETRA features for each TIP specification (as described in the TIC-RT). The main interoperable TETRA features result depend on a set of sub-feature, the outcomes associated to each sub-feature are directly derived from the analysis of the performed test cases.

The results associated to each feature and sub-feature are shown in the "Feature compliance report" table below. The main features are indicated with grey background and the associated sub-features (or second level features) have light blue background.

The outcome assigned to a sub-feature as shown on page 2, is derived by the Feature compliance report tables.

Outcome	Definition
Certified	All required tests have been performed and passed
Partial	Not all the required tests have been performed but none have failed
-	Feature cannot be certified e.g. it is not supported by at least one product, no tests were performed, or some tests were performed but at least one failed

The outcome is derived from the verdict assigned to a sub feature which is the result of an analysis of the test case results listed in the Test Report. The verdict assigned to each sub-feature is derived from one or several test case results or test steps result, the TETRA Interoperability requirement tables (TIC-RTs) indicate the link between sub-features and test cases for the certified set of equipment capabilities (see Test Report).

Verdict	Definition
Passed	All mandated tests or steps of tests linked to this functionality (as per TIC-RT indication) are compliant with the TIP specification relevant to this feature.
Incomplete	Not all Mandated tests (as per TIC-RT indication) have been executed
Failed	At least one of mandated test or steps of tests linked to this functionality failed to match the TIP specification relevant to this feature.

The verdict associated to the feature gives also indication about the method used to test that feature. The allowed testing Methods are listed in the table below, a complete description of the procedures and constraints associated to each of them can be found in the "TPD001-01 TETRA Interoperability

Certification Process Description" document.

Testing Method	Description
Complete	All mandated tests associated to the feature have been executed
Spot	Only a selection of the mandatory test cases associated to the feature has been executed during the test session. These tests are a subset of the tests performed on an equivalent software which has been "completely" tested against the same functionality on a different equipment, see manufacturer declaration in the associated Test Report
Regression	Only a selection of the mandatory test cases associated to the feature has been executed during the test session. These tests are a subset of the tests performed on a previous version of the same software which has been "completely" tested in a previous test session against the same functionality, see manufacturer definition in the associated Test Report
Regression on spot	The regression method has been applied on the verdicts based on the spot testing method
Witnessed	The TIP heading lines in the Feature Compliance Report indicate whether each TIP is partially or fully witnessed by the Certification Body. Additionally, for a partially-witnessed TIP, the number of witnessed test cases that passed is shown for each the feature and sub-feature. There may have been some un-witnessed passed tests and they will have been found to be successful based on the log file evaluation.

Depending on equipment capabilities declared by the manufacturer, some features or sub features cannot be tested. The following table describes meaning of the used abbreviation:

Indication	Definition
Not supported	The SwMI and/or MS do not support the minimum features required to verify these items

ISCTI has made every effort to ensure that every result has been correctly evaluated in accordance with the relevant TIPs, Test Plans and TIC-RTs. ISCTI has no liability for the test results, or towards the manufacturers.

The table on the following page lists HW and SW releases of SwMI and Terminal under test in the last four test sessions and the used TIP specifications, Test Plans and TIC-RTs.

This Certificate and Certificates from previous test sessions are available on the TETRA + Critical Communications Association web site (<http://www.tandcca.com/interop/page/12476>).

The feature results are shown in the tables below.

Information on equipment under test and document references

Test Session Date/Place	Motorola Krakow December 2013			
SwMI Type	Dimetra IP R7.1			
SwMI HW Release	Dimetra IP R7.1			
SwMI SW Release	7.1			
Terminal Type	MTP3150			
Terminal HW Release	PT912OHE			
Terminal SW Release	MR10.7			
TIP Specs and TIP Compliance Test Plans				
Core	TTR001-01 v6.0.0 IOP001-01 v3.0.0 TIC-RT001-01 v260			
SDS	TTR001-02 v2.0.1 IOP001-02 v2.0.0 TIC-RT001-02 v213			

DGNA	TTR001-03 v2.0.0 IOP001-03 v2.0.1 TIC-RT001-03 v221			
Auth	TTR001-04 v3.0.0 IOP001-04 v2.0.0 TIC-RT001-04 v223			
PD	TTR001-05 v3.0.0 IOP001-05 v3.0.5 TIC-RT001-05 v303			
AL	TTR001-09 v2.0.0 IOP001-09 v1.1.0 TIC-RT001-09 v122			
AIE	TTR001-11 v3.0.3 IOP001-11 v3.0.2 TIC-RT001-11 v323			
SI	TTR001-12 v1.0.0 IOP001-12 v1.0.0 TIC-RT001-12 v127			
ED	TTR001-13 v2.0.0 IOP001-13 v1.0.0 TIC-RT001-13 v146			

Feature compliance report

Test Session	Motorola Krakow December 2013			
Core				
Registration	Spot 0_pass_of_3			
ITSI attach	Spot 0_pass_of_1			
SwMI initiated location updating	Spot 0_pass_of_1			
LA timer based Periodic location updating	Not Supported			
De-registration	Spot 0_pass_of_1			
Group Management	Spot 0_pass_of_9			
Single group attachment	Spot 0_pass_of_4			
Multiple group attachment	Spot 0_pass_of_3			
MS initiated group detachment	Spot 0_pass_of_2			
SwMI initiated group management	Not Supported			
Group call	Spot 0_pass_of_9			
Normal group call	Spot 0_pass_of_3			
Late entry	Spot 0_pass_of_1			
Priority Group scanning	Spot 0_pass_of_3			
Call setup modifications	Spot 0_pass_of_1			
Resource Queuing based on Call Priority	Spot 0_pass_of_1			
Broadcast Call	Not Supported			
Limited coverage notification	Not Supported			

Individual call	PASSED Spot 1_pass_of_7			
Simplex individual call	Spot 0_pass_of_3			
Duplex individual call	PASSED Spot 1_pass_of_2			
Call setup modifications	Not Supported			
Resource Queuing based on Call Priority	Spot 0_pass_of_2			
Indication of imminent call disconnection	Not Supported			
Status messages	Spot 0_pass_of_1			
Individual addressed Status transfer	Not Supported			
Group addressed Status transfer	Spot 0_pass_of_1			
Pre-emptive Priority Call	Spot 0_pass_of_1			
Pre-emption of Resources	Spot 0_pass_of_1			
Pre-emption of Busy Users	Not Supported			
Emergency Call	PASSED Spot 1_pass_of_2			
Pre-emption of Resources	Spot 0_pass_of_1			
Pre-emption of Busy Users	PASSED Complete 1_pass_of_1			
Call setup modifications	Not Supported			
Call disconnection by non-call owner	Not Supported			
Cell Re-selection	PASSED Spot 1_pass_of_16			
Undeclared	Spot 0_pass_of_1			
Unannounced	PASSED Spot 1_pass_of_7			
Announced - with Call Restoration	PASSED Spot 0_pass_of_8			
Announced - without Call Restoration	Not Supported			
Expedited	Not Supported			

PSTN interconnect	PASSED Spot 2_pass_of_4			
TETRA Originated Call	PASSED Spot 1_pass_of_2			
PSTN Originated Call	Spot 0_pass_of_1			
DTMF over-dial	PASSED Complete 1_pass_of_1			
Emergency Telephone Calls	Not Supported			
MS-ISDN Numbering				
MS ISDN - Voice Call	Not Supported			
MS-ISDN Status	Not Supported			
In Call Signalling	PASSED Spot 1_pass_of_5			
Slow Signalling on Traffic Channel (SACCH)	PASSED Spot 1_pass_of_4			
Fast Signalling on Traffic Channel (FACCH)	Spot 0_pass_of_1			
Subscriber Class Procedures	Spot Incomplete 0_pass_of_5			
Cell Selection based on Subscriber Class	Spot Incomplete 0_pass_of_2			
Subscriber Class Delivery during Location Update	Not Supported			
Use of Preferred Subscriber Classes	Spot Incomplete 0_pass_of_3			
Common Secondary Control Channels	PASSED Spot 3_pass_of_7			
One C-SCCH per cell	PASSED Spot 2_pass_of_4			
Two C-SCCH per cell	PASSED Spot 2_pass_of_3			
Three C-SCCH per cell	PASSED Spot 1_pass_of_2			
BS Fallback Operation	PASSED Spot 3_pass_of_9			
Switch to/from BS Fallback Operation	PASSED Spot 1_pass_of_2			
Roaming with BS Fallback Operation	Spot 0_pass_of_2			
Services with BS Fallback Operation	PASSED Spot 2_pass_of_5			

Energy Economy Mode	PASSED Spot 2_pass_of_3			
Energy Economy Mode Operation	PASSED Spot 2_pass_of_3			
Transmit Inhibit	PASSED Spot 6_pass_of_8			
TXI Activation & De-Activation without Status message	PASSED Spot 3_pass_of_4			
TXI Activation & De-Activation with Status message	PASSED Spot 2_pass_of_3			
Receipt of group addressed service during TXI	PASSED Complete 1_pass_of_1			
Mixed band operation	Spot 0_pass_of_4			
Mixed band operation, inter-cell	Spot 0_pass_of_4			
Mixed band operation, intra-cell	Spot 0_pass_of_3			
Mixed band operation, Full	Spot 0_pass_of_3			
Short Data Service (SDS)				
SDS Type 1, 2 or 3				
SDS Type 1	Not Supported			
SDS Type 2	Not Supported			
SDS Type 3	Not Supported			
SDS-TL	PASSED Spot 2_pass_of_8			
Individually Addressed	Spot 0_pass_of_2			
Group Addressed	PASSED Spot 1_pass_of_2			
Using MS-ISDN dialling	Not Supported			
Using UCS2 coding scheme	PASSED Spot 1_pass_of_2			
Using 7-bit coding scheme	Spot 0_pass_of_1			
Using 8-bit Latin 1 coding scheme	Spot 0_pass_of_2			
Using 8-bit Latin 5 coding scheme	Not Supported			
Using 8-bit Latin 9 coding scheme	Complete			

Store and Forward	PASSED Spot 1_pass_of_3			
Individually Addressed	PASSED Spot 1_pass_of_3			
Group Addressed	Not Supported			
Dynamic Group Number Assignment (DGNA)				
Support for individually addressed DGNA	PASSED Spot 2_pass_of_6			
Support for individually addressed DGNA assignment without attachment	PASSED Spot 1_pass_of_4			
Support for individually addressed DGNA assignment with attachment as selected group	Not Supported			
Support for individually addressed DGNA assignment with attachment as scanned group	Not Supported			
Support for individually addressed DGNA assignment with rejected attachment	Not Supported			
Support for individually addressed assignment for pre- programmed group	PASSED Spot 1_pass_of_4			
Support for group addressed DGNA	Spot Incomplete 1_pass_of_6			
Support for group addressed DGNA assignment	Spot Incomplete 0_pass_of_3			
Management of 'group assignment lifetime'	Spot Incomplete 0_pass_of_2			
Support for group addressed DGNA deassignment	PASSED Complete 1_pass_of_1			

Tolerance of unsupported DGNA functions				
MS tolerance of unsupported individual addressed DGNA signalling	Not Supported			
MS tolerance of unsupported group addressed DGNA signalling	Not Supported			
Authentication				
SwMI Initiated (non-mutual) Authentication	Spot 0_pass_of_3			
Attach with authentication	Spot 0_pass_of_1			
Roaming with authentication	Spot 0_pass_of_1			
SwMI rejects MS during authentication	Spot 0_pass_of_1			
MS rejects SwMI during authentication	Not Supported			
SwMI Initiated Authentication made Mutual by MS	PASSED Spot 1_pass_of_2			
Attach with authentication	Spot 0_pass_of_1			
Roaming with authentication	PASSED Complete 1_pass_of_1			
TEI Query				
TEI Query Operation	Not Supported			
TETRA Packet Data				
Context Management	PASSED Spot 1_pass_of_11			
Context Activation	PASSED Spot 1_pass_of_7			
User authentication	Spot 0_pass_of_4			

Single Slot Packet Data	PASSED Spot 2_pass_of_10			
Data Transfer	PASSED Spot 1_pass_of_7			
Cell re-selection	PASSED Spot 1_pass_of_3			
Multi Slot Packet Data	PASSED Spot 2_pass_of_4			
Data Transfer	PASSED Spot 2_pass_of_4			
TEDS				
TEDS with Context Activation	Not Supported			
TEDS Data Transmission	Not Supported			
TEDS Cell Reselection	Not Supported			
Mixed band operation	PASSED Spot 1_pass_of_2			
Mixed band operation, inter-cell	PASSED Spot 1_pass_of_2			
Mixed band operation, intra-cell	PASSED Spot 1_pass_of_2			
Mixed band operation, Full	PASSED Spot 1_pass_of_2			
TETRA Ambience Listening (SS-AL)				
Ambience Listening	PASSED Spot 1_pass_of_5			
SS-AL Call Setup	PASSED Spot 1_pass_of_2			
MS initiated SS-AL disconnection	Spot 0_pass_of_3			
No Indication to affected user	PASSED Spot 1_pass_of_5			

Interaction with Transmit Inhibit	PASSED Complete 1_pass_of_1			
AL can override TxI	Not Supported			
AL cannot override TxI	PASSED Complete 1_pass_of_1			
Air Interface Encryption				
Security Class 2 Air Interface Encryption	FAILED Spot 7_pass_of_20			
Location Updating and AI Signalling Protection	PASSED Spot 3_pass_of_7			
TM-SCK provisioning during location updating	Spot 0_pass_of_2			
Communications between parties using encryption	Spot 0_pass_of_2			
Communications between clear and encrypted parties	Spot 0_pass_of_3			
Communications between encrypted parties on a channel designated to operate in clear	PASSED Spot 1_pass_of_2			
OTAR and Change of TM-SCK	Spot 0_pass_of_2			
Change of TM-SCK	FAILED Spot 1_pass_of_4			
Packet Data with Class 2 Air Interface Encryption	PASSED Complete 2_pass_of_2			
Security Class 3 Air Interface Encryption	Spot Incomplete 4_pass_of_21			
Location Updating and AI Signalling Protection	Spot Incomplete 1_pass_of_9			
DCK Forwarding at MS request	Not Supported			
DCK Forwarding by SwMI (without MS request)	Spot 0_pass_of_1			
DCK Retrieval	PASSED Spot 1_pass_of_4			

CCK provisioning during location updating	Spot Incomplete 0_pass_of_4			
Communications between parties using encryption	PASSED Spot 1_pass_of_2			
Communications between clear and encrypted parties	Spot 0_pass_of_3			
Communications between encrypted parties on a channel designated to operate in clear	PASSED Spot 1_pass_of_2			
OTAR of CCK	Spot 0_pass_of_2			
Change of CCK	Spot 0_pass_of_4			
Packet Data with Class 3 Air Interface Encryption	PASSED Spot 1_pass_of_2			
Security Class 3G Air Interface Encryption	Spot Incomplete 1_pass_of_9			
GCK Key Association setting	PASSED Spot 1_pass_of_3			
Communications between parties using encryption	Spot 0_pass_of_2			
Communications between clear and encrypted parties	Spot 0_pass_of_1			
OTAR of GCK	Spot 0_pass_of_2			
Change of GCK	Spot Incomplete 0_pass_of_3			
Management of CMG and GSKO	Spot 0_pass_of_5			
OTAR and change of CMG and GSKO	Spot 0_pass_of_5			
Key Status demand	PASSED Spot 2_pass_of_4			
SCK Key Status demand	PASSED Complete 2_pass_of_2			
GCK Key Status demand	Spot 0_pass_of_1			

GSKO Key Status demand	Spot 0_pass_of_1			
Change of Security Class for Fallback operation	Spot 0_pass_of_12			
Seamless change to Security Class 2 for BS Fallback operation	Spot 0_pass_of_10			
Non-seamless change to Security Class 2 for BS Fallback operation	Not Supported			
Provisioning of TM-SCK for fallback to Security Class 2 operation	Spot 0_pass_of_2			
Change to Security Class 1 for BS Fallback operation	Not Supported			
Change of Security Class (other than for Fallback operation)	PASSED Spot 1_pass_of_5			
Change between Security Class 3 and Security Class 3G	PASSED Spot 1_pass_of_2			
Change between Security Class 2 and Security Class 3	Spot 0_pass_of_2			
Change from Security Class 3G to Security Class 2	Spot 0_pass_of_1			
Key Management for Secure Direct Mode Operation	PASSED Spot 1_pass_of_3			
OTAR of DM-SCK	PASSED Spot 1_pass_of_3			
Change of DM-SCK	Spot 0_pass_of_2			
Service Interaction				
MS initiated Service Interaction	Spot 0_pass_of_3			
MS initiated Circuit Mode Call during another Circuit Mode Call	Spot 0_pass_of_1			

MS initiated Circuit Mode Call during Packet Mode Transfer	Spot 0_pass_of_2			
MS initiated Packet Mode Transfer during Circuit Mode Call	Not Supported			
SwMI initiated Service Interaction	PASSED Spot 2_pass_of_6			
SwMI initiated Circuit Mode Call during another Circuit Mode Call	PASSED Spot 2_pass_of_4			
SwMI initiated Circuit Mode Call during Packet Mode Transfer	Spot 0_pass_of_2			
SwMI initiated Packet Mode Transfer during Circuit Mode Call	Not Supported			
Call Waiting				
Call Waiting in Individual Call	Not Supported			
Call Waiting in Group Call	Not Supported			
Enable Disable				
Enable and temporary disable of an MS	PASSED Spot 1_pass_of_8			
Enable and temporary disable of an MS without authentication	Spot 0_pass_of_2			
Enable and temporary disable of an MS with authentication	Not Supported			
Registration of a temporary disabled MS	PASSED Spot 1_pass_of_2			
Rejection of applicable invalid enable/disable requests	Spot 0_pass_of_3			
Removable SIMs do not affect the subscriber or equipment that has been enabled/disabled	Not Supported			

Disabling of an MS during a call or while on the PDCH	Spot 0_pass_of_1			
Permanent disable of an MS	PASSED Spot 1_pass_of_2			
Permanent disable of an MS with authentication	PASSED Complete 1_pass_of_1			
Permanently Disabled MS cannot send air interface signalling	Spot 0_pass_of_1			