

# TETRA Interoperability Certificate

**Teltronic, NEBULA, SwMI –  
Unimo, UM1500, Terminal**

Zaragoza, September 2012

Latest Certified SwMI SW Release:	12.20.50	Latest Certified Terminal SW Release:	B1.4.3
Latest Certified SwMI HW Release:	12.20.18.23	Latest Certified Terminal HW Release:	MD15-R1.0

ISCTI (Istituto Superiore delle Comunicazioni e delle Tecnologie dell'Informazione) certifies, that the Teltronic, NEBULA, SwMI and the Unimo, UM1500, terminal have been subject to interoperability testing for the "certified" features listed on second page of this certificate, in accordance with the TETRA Interoperability Profiles, TIP compliance Test Plan and related TETRA interoperability requirement tables.

The table lists all the available TETRA interoperability profiles, and summarizes the main functionalities of every profile according to the TETRA interoperability requirement tables.

A feature is "Certified" when it has been successfully tested during the last test session with one of the testing method described in the TETRA process document part 1 (TPD001-01).

A breakdown into the feature details is given in the Feature Compliance Overview section of this certificate.

This certificate has been issued following a multiple test session between Teltronic and Unimo on September 2012. Detailed test results are listed in the Test Report associated to this Certificate. Details and explanation about the procedure used to provide verdicts are in the TIC process TPD001-01.

**IOP test engineer**



Massimo Proietti

**Radio Office Manager**

Giuseppe Pierri



ISCTI - V.le America 201, 00144 Rome, Italy  
Ph.: +39 06 5444 2663, Fax: +39 06 5410904  
e-mail: [tetra\\_ctc.iscom@mise.gov.it](mailto:tetra_ctc.iscom@mise.gov.it)  
Web: [www.mise.gov.it](http://www.mise.gov.it)

**Date of issue**

**4 March 2013**

**v 1**

## Certified features

<b>Tetra Association TTR001-01:Core</b>	
<b>Registration</b>	Certified
<b>Group Management</b>	Certified
<b>Group call</b>	-
<b>Individual call</b>	-
<b>Status messages</b>	Certified
<b>Pre-emptive Priority Call</b>	-
<b>Emergency Call</b>	-
<b>Cell Re-selection</b>	Certified
<b>PSTN interconnect</b>	-
<b>MS-ISDN Numbering</b>	-
<b>In Call Signalling</b>	-
<b>Subscriber Class Procedures</b>	-
<b>Common Secondary Control Channels</b>	-
<b>BS Fallback Operation</b>	-
<b>Energy Economy Mode</b>	-
<b>Transmit Inhibit</b>	-
<b>Mixed band operation</b>	-
<b>Tetra Association TTR001-02:SDS</b>	
<b>SDS Type 1, 2 or 3</b>	Certified
<b>SDS-TL</b>	Certified
<b>Store and Forward</b>	-

<b>Tetra Association TTR001-04:Auth</b>	
<b>SwMI Initiated (non-mutual) Authentication</b>	Certified
<b>SwMI Initiated Authentication made Mutual by MS</b>	Certified
<b>TEI Query</b>	-
<b>Tetra Association TTR001-05:PD</b>	
<b>Context Management</b>	Certified
<b>Single Slot Packet Data</b>	Certified
<b>Multi Slot Packet Data</b>	-
<b>TEDS</b>	-
<b>Mixed band operation</b>	-

# Feature Compliance Overview

The first pages of this certificate provide an indication about the main interoperable TETRA features for each TIP specification (as described in the TIC-RT). The main interoperable TETRA features result depend on a set of sub-feature, the outcomes associated to each sub-feature are directly derived from the analysis of the performed test cases.

The results associated to each feature and sub-feature are shown in the "Feature compliance report" table below. The main features are indicated with grey background and the associated sub-features (or second level features) have white background.

The outcome assigned to a sub-feature as shown on page 2, is derived by the Feature compliance report tables.

Outcome	Definition
<b>Certified</b>	All required tests have been performed and passed
<b>Partial</b>	Not all the required tests have been performed but none have failed
-	Feature cannot be certified e.g. it is not supported by at least one product, no tests were performed, or some tests were performed but at least one failed

The outcome is derived from the verdict assigned to a sub feature which is the result of an analysis of the test case results listed in the Test Report. The verdict assigned to each sub-feature is derived from one or several test case results or test steps result, the TETRA Interoperability requirement tables (TIC-RTs) indicate the link between sub-features and test cases for the certified set of equipment capabilities (see Test Report).

Verdict	Definition
<b>Passed</b>	All mandated tests or steps of tests linked to this functionality (as per TIC-RT indication) are compliant with the TIP specification relevant to this feature.
<b>Incomplete</b>	Not all Mandated tests (as per TIC-RT indication) have been executed
<b>Failed</b>	At least one of mandated test or steps of tests linked to this functionality failed to match the TIP specification relevant to this feature.

The verdict associated to the feature gives also indication about the method used to test that feature. The allowed testing Methods are listed in the table below, a complete description of the procedures and constraints associated to each of them can be found in the "TPD001-01 TETRA Interoperability Certification Process Description" document.

Testing Method	Description
<b>Complete</b>	All mandated tests associated to the feature have been executed
<b>Spot</b>	Only a selection of the mandatory test cases associated to the feature has been executed during the test session. These tests are a subset of the tests performed on an equivalent software which has been "completely" tested against the same functionality on a different equipment, see manufacturer declaration in the associated Test Report
<b>Regression</b>	Only a selection of the mandatory test cases associated to the feature has been executed during the test session. These tests are a subset of the tests performed on a previous version of the same software which has been "completely" tested in a previous test session against the same functionality, see manufacturer definition in the associated Test Report
<b>Regression on spot</b>	The regression method has been applied on the verdicts based on the spot testing method
<b>Witnessed</b>	The CB has witnessed that the identified number of tests were successfully passed. Other tests have been found to be successful based on the log file evaluation.

Depending on equipment capabilities declared by the manufacturer, some features or sub features cannot be tested. The following table describes meaning of the used abbreviation:

Indication	Definition
<b>Not supported</b>	The SwMI and/or MS do not support the minimum features required to verify these items

ISCTI has made every effort to ensure that every result has been correctly evaluated in accordance with the relevant TIPs, Test Plans and TIC-RTs. ISCTI has no liability for the test results, or towards the manufacturers.

The table on the following page lists HW and SW releases of SwMI and Terminal under test in the last four test sessions and the used TIP specifications, Test Plans and TIC-RTs.

This Certificate and Certificates from previous test sessions are available on the TETRA + Critical Communications Association web site (<http://www.tandcca.com/interop/page/12476>).

The feature results are shown in the tables below.

## Information on equipment under test and document references

Test Session Date/Place	Teltronic, Zaragoza, September 2012				
SwMI Type	NEBULA				
SwMI HW Release	12.20.18.23				
SwMI SW Release	12.20.50				
Terminal Type	UM1500				
Terminal HW Release	MD15-R1.0				
Terminal SW Release	B1.4.3				
TIP Specs and TIP Compliance Test Plans					
Core	TTR001-01	v6.0.0			
	IOP001-01	v3.0.0			
	TIC-RT001-01	v2.5.4			
SDS	TTR001-02	v2.1.1			
	IOP001-02	v2.0.0			
	TIC-RT001-02	v2.1.2			
Auth	TTR001-04	v3.0.0			
	IOP001-04	v2.0.0			
	TIC-RT001-04	v2.2.3			
PD	TTR001-05	v3.0.0			
	IOP001-05	v3.0.5			
	TIC-RT001-05	v3.0.2			

## Feature compliance report

Test Session	Teltronic Zaragoza September 2012			
<b>Core</b>				
Registration	PASSED Complete 3_pass_of_3			
ITSI attach	PASSED Complete 2_pass_of_2			
SwMI initiated location updating	Not Supported			
LA timer based Periodic location updating	Not Supported			
De-registration	PASSED Complete 1_pass_of_1			
Group Management	PASSED Complete 1_pass_of_1			
Single group attachment	PASSED Complete 1_pass_of_1			
Multiple group attachment	Not Supported			
MS initiated group detachment	Not Supported			
SwMI initiated group management	Not Supported			
Group call				
Normal group call	Not Supported			
Late entry	Not Supported			
Priority Group scanning	Not Supported			
Call setup modifications	Not Supported			
Resource Queuing based on Call Priority	Not Supported			
Broadcast Call	Not Supported			
Limited coverage notification	Not Supported			



Individual call				
Simplex individual call	Not Supported			
Duplex individual call	Not Supported			
Call setup modifications	Not Supported			
Resource Queuing based on Call Priority	Not Supported			
Indication of imminent call disconnection	Not Supported			
Status messages	PASSED Complete 1_pass_of_1			
Individual addressed Status transfer	PASSED Complete 1_pass_of_1			
Group addressed Status transfer	Not Supported			
Pre-emptive Priority Call				
Pre-emption of Resources	Not Supported			
Pre-emption of Busy Users	Not Supported			
Emergency Call				
Pre-emption of Resources	Not Supported			
Pre-emption of Busy Users	Not Supported			
Call setup modifications	Not Supported			
Call disconnection by non-call owner	Not Supported			
Cell Re-selection	PASSED Complete 1_pass_of_1			
Undeclared	PASSED Complete 1_pass_of_1			
Unannounced	Not Supported			
Announced - with Call Restoration	Not Supported			
Announced - without Call Restoration	Not Supported			
Expedited	Not Supported			
PSTN interconnect				

TETRA Originated Call	Not Supported			
PSTN Originated Call	Not Supported			
DTMF over-dial	Not Supported			
Emergency Telephone Calls	Not Supported			
MS-ISDN Numbering				
MS ISDN - Voice Call	Not Supported			
MS-ISDN Status	Not Supported			
In Call Signalling				
Slow Signalling on Traffic Channel (SACCH)	Not Supported			
Fast Signalling on Traffic Channel (FACCH)	Not Supported			
Subscriber Class Procedures				
Cell Selection based on Subscriber Class	Not Supported			
Subscriber Class Delivery during Location Update	Not Supported			
Use of Preferred Subscriber Classes	Not Supported			
Common Secondary Control Channels				
One C-SCCH per cell	Not Supported			
Two C-SCCH per cell	Not Supported			
Three C-SCCH per cell	Not Supported			
BS Fallback Operation				
Switch to/from BS Fallback Operation	Not Supported			
Roaming with BS Fallback Operation	Not Supported			
Services with BS Fallback Operation	Not Supported			
Energy Economy Mode				
Energy Economy Mode Operation	Not Supported			

Transmit Inhibit				
TXI Activation & De-Activation without Status message	Not Supported			
TXI Activation & De-Activation with Status message	Not Supported			
Receipt of group addressed service during TXI	Not Supported			
Mixed band operation				
Mixed band operation, inter-cell	Not Supported			
Mixed band operation, intra-cell	Not Supported			
Mixed band operation, Full	Not Supported			
<b>Short Data Service (SDS)</b>				
SDS Type 1, 2 or 3	PASSED Complete 3_pass_of_3			
SDS Type 1	PASSED Complete 1_pass_of_1			
SDS Type 2	PASSED Complete 1_pass_of_1			
SDS Type 3	PASSED Complete 1_pass_of_1			
SDS-TL	PASSED Complete 5_pass_of_5			
Individually Addressed	PASSED Complete 1_pass_of_1			
Group Addressed	PASSED Complete 2_pass_of_2			
Using MS-ISDN dialling	Not Supported			
Using UCS2 coding scheme	PASSED Complete 2_pass_of_2			
Using 7-bit coding scheme	Not Supported			
Store and Forward				
Individually Addressed	Not Supported			
Group Addressed	Not Supported			
<b>Authentication</b>				
SwMI Initiated (non-mutual) Authentication	PASSED Complete 3_pass_of_3			

Attach with authentication	PASSED Complete 1_pass_of_1			
Roaming with authentication	PASSED Complete 1_pass_of_1			
SwMI rejects MS during authentication	PASSED Complete 1_pass_of_1			
MS rejects SwMI during authentication	Not Supported			
SwMI Initiated Authentication made Mutual by MS	PASSED Complete 2_pass_of_2			
Attach with authentication	PASSED Complete 1_pass_of_1			
Roaming with authentication	PASSED Complete 1_pass_of_1			
TEI Query				
TEI Query Operation	Not Supported			
<b>TETRA Packet Data</b>				
Context Management	PASSED Complete 9_pass_of_9			
Context Activation	PASSED Complete 7_pass_of_7			
User authentication	PASSED Complete 2_pass_of_2			
Single Slot Packet Data	PASSED Complete 7_pass_of_7			
Data Transfer	PASSED Complete 4_pass_of_4			
Cell re-selection	PASSED Complete 3_pass_of_3			
Multi Slot Packet Data				
Data Transfer	Not Supported			
TEDS				
TEDS with Context Activation	Not Supported			
TEDS Data Transmission	Not Supported			
TEDS Cell Reselection	Not Supported			

Mixed band operation				
Mixed band operation, inter-cell	Not Supported			
Mixed band operation, intra-cell	Not Supported			
Mixed band operation, Full	Not Supported			