

# TETRA Interoperability Certificate

## Rohill, Tetra Node, SwMI – Sepura, SRG3900, Terminal

Hoogeveen, November 2014

Latest Certified SwMI SW Release:	3.00	Latest Certified Terminal SW Release:	1711 013 03577
Latest Certified SwMI HW Release:	2.50	Latest Certified Terminal HW Release:	MSUTW201T2C0G00

ISCTI (Istituto Superiore delle Comunicazioni e delle Tecnologie dell'Informazione) certifies, that the Rohill, Tetra Node, SwMI and the Sepura, SRG3900, terminal have been subject to interoperability testing for the “certified” features listed on second page of this certificate, in accordance with the TETRA Interoperability Profiles, TIP compliance Test Plan and related TETRA interoperability requirement tables.

The table lists all the available TETRA interoperability profiles, and summarizes the main functionalities of every profile according to the TETRA interoperability requirement tables.

A feature is “Certified” when it has been successfully tested during the last test session with one of the testing method described in the TETRA process document part 1 (TPD001-01).

A breakdown into the feature details is given in the Feature Compliance Overview section of this certificate.

This certificate has been issued following a fully witnessed single test session between Rohill and Sepura on November 2014. Detailed test results are listed in the Test Report associated to this Certificate. Details and explanation about the procedure used to provide verdicts are in the TIC process TPD001-01.

**IOP test engineer**

**Radio Office Manager**

  
Roberto Feroci

Giuseppe Pierri  


ISCTI - V.le America 201, 00144 Rome, Italy  
Ph.: +39 06 5444 2663, Fax: +39 06 5410904  
e-mail: [tetra\\_ctc.iscom@mise.gov.it](mailto:tetra_ctc.iscom@mise.gov.it)  
Web: [www.mise.gov.it](http://www.mise.gov.it)

**Date of issue**  
**15 December 2014**  
**v 1**

## Certified features

<b>Tetra Association TTR001-01:Core</b>	
<b>Registration</b>	Certified
<b>Group Management</b>	Certified
<b>Group call</b>	Certified
<b>Individual call</b>	Certified
<b>Status messages</b>	Certified
<b>Pre-emptive Priority Call</b>	Certified
<b>Emergency Call</b>	Certified
<b>Cell Re-selection</b>	Certified
<b>PSTN interconnect</b>	Certified
<b>MS-ISDN Numbering</b>	Certified
<b>In Call Signalling</b>	Certified
<b>Subscriber Class Procedures</b>	Certified
<b>Common Secondary Control Channels</b>	Certified
<b>BS Fallback Operation</b>	Certified
<b>Energy Economy Mode</b>	-
<b>Transmit Inhibit</b>	Certified
<b>Mixed band operation</b>	-
<b>Tetra Association TTR001-02:SDS</b>	
<b>SDS Type 1, 2 or 3</b>	-
<b>SDS-TL</b>	Certified
<b>Store and Forward</b>	-
<b>Tetra Association TTR001-03:DGNA</b>	
<b>Support for individually addressed DGNA</b>	Certified
<b>Support for group addressed DGNA</b>	Certified
<b>Tolerance of unsupported DGNA functions</b>	-

<b>Tetra Association TTR001-04:Auth</b>	
<b>SwMI Initiated (non-mutual) Authentication</b>	Certified
<b>SwMI Initiated Authentication made Mutual by MS</b>	Certified
<b>TEI Query</b>	-
<b>Tetra Association TTR001-05:PD</b>	
<b>Context Management</b>	Certified
<b>Single Slot Packet Data</b>	Certified
<b>Multi Slot Packet Data</b>	Certified
<b>TEDS</b>	-
<b>Mixed band operation</b>	-
<b>Tetra Association TTR001-09:AL</b>	
<b>Ambience Listening</b>	Certified
<b>Interaction with Transmit Inhibit</b>	Certified
<b>Tetra Association TTR001-10:E2EE</b>	
<b>E2EE Voice Call</b>	Certified
<b>Tetra Association TTR001-11:AIE</b>	
<b>Security Class 2 Air Interface Encryption</b>	Certified
<b>Security Class 3 Air Interface Encryption</b>	Certified
<b>Security Class 3G Air Interface Encryption</b>	-
<b>Change of CMG and GSKO</b>	-
<b>Key Status demand</b>	-
<b>Change of Security Class for Fallback operation</b>	-
<b>Change of Security Class (other than for Fallback operation)</b>	-
<b>Key Management for Secure Direct Mode Operation</b>	-

## Feature Compliance Overview

The first pages of this certificate provide an indication about the main interoperable TETRA features for each TIP specification (as described in the TIC-RT). The main interoperable TETRA features result depend on a set of sub-feature, the outcomes associated to each sub-feature are directly derived from the analysis of the performed test cases.

The results associated to each feature and sub-feature are shown in the "Feature compliance report" table below. The main features are indicated with grey background and the associated sub-features (or second level features) have light blue background.

The outcome assigned to a sub-feature as shown on page 2, is derived by the Feature compliance report tables.

Outcome	Definition
<b>Certified</b>	All required tests have been performed and passed
<b>Partial</b>	Not all the required tests have been performed but none have failed
-	Feature cannot be certified e.g. it is not supported by at least one product, no tests were performed, or some tests were performed but at least one failed

The outcome is derived from the verdict assigned to a sub feature which is the result of an analysis of the test case results listed in the Test Report. The verdict assigned to each sub-feature is derived from one or several test case results or test steps result, the TETRA Interoperability requirement tables (TIC-RTs) indicate the link between sub-features and test cases for the certified set of equipment capabilities (see Test Report).

Verdict	Definition
<b>Passed</b>	All mandated tests or steps of tests linked to this functionality (as per TIC-RT indication) are compliant with the TIP specification relevant to this feature.
<b>Incomplete</b>	Not all Mandated tests (as per TIC-RT indication) have been executed
<b>Failed</b>	At least one of mandated test or steps of tests linked to this functionality failed to match the TIP specification relevant to this feature.

The verdict associated to the feature gives also indication about the method used to test that feature.

The allowed testing Methods are listed in the table below, a complete description of the procedures and constraints associated to each of them can be found in the "TPD001-01 TETRA Interoperability Certification Process Description" document.

Testing Method	Description
<b>Complete</b>	All mandated tests associated to the feature have been executed
<b>Spot</b>	Only a selection of the mandatory test cases associated to the feature has been executed during the test session. These tests are a subset of the tests performed on an equivalent software which has been "completely" tested against the same functionality on a different equipment, see manufacturer declaration in the associated Test Report
<b>Regression</b>	Only a selection of the mandatory test cases associated to the feature has been executed during the test session. These tests are a subset of the tests performed on a previous version of the same software which has been "completely" tested in a previous test session against the same functionality, see manufacturer definition in the associated Test Report
<b>Regression on spot</b>	The regression method has been applied on the verdicts based on the spot testing method
<b>Witnessed</b>	The TIP heading lines in the Feature Compliance Report indicate whether each TIP is partially or fully witnessed by the Certification Body. Additionally, for a partially-witnessed TIP, the number of witnessed test cases that passed is shown for each the feature and sub-feature. There may have been some un-witnessed passed tests and they will have been found to be successful based on the log file evaluation.

Depending on equipment capabilities declared by the manufacturer, some features or sub features cannot be tested. The following table describes meaning of the used abbreviation:

Indication	Definition
<b>Not supported</b>	The SwMI and/or MS do not support the minimum features required to verify these items

ISCTI has made every effort to ensure that every result has been correctly evaluated in accordance

with the relevant TIPs, Test Plans and TIC-RTs. ISCTI has no liability for the test results, or towards the manufacturers.

The table on the following page lists HW and SW releases of SwMI and Terminal under test in the last four test sessions and the used TIP specifications, Test Plans and TIC-RTs.

This Certificate and Certificates from previous test sessions are available on the TETRA + Critical Communications Association web site (<http://www.tandcca.com/interop/page/12476>).

The feature results are shown in the tables below.

### Information on equipment under test and document references

Test Session Date/Place	Rohill Hoogeveen November 2014			
SwMI Type	Tetra Node			
SwMI HW Release	2.50			
SwMI SW Release	3.00			
Terminal Type	SRG3900			
Terminal HW Release	MSUTW201T2C0G00			
Terminal SW Release	1711 013 03577			
TIP Specs and TIP Compliance Test Plans				
Core	TTR001-01 v6.0.0 IOP001-01 v3.0.0 TIC-RT001-01 v2.6.1			

SDS	TTR001-02 v2.0.1 IOP001-02 v2.0.0 TIC-RT001-02 v2.1.3			
DGNA	TTR001-03 v2.0.0 IOP001-03 v2.0.1 TIC-RT001-03 v2.2.2			
Auth	TTR001-04 v3.0.0 IOP001-04 v2.0.0 TIC-RT001-04 v2.2.5			
PD	TTR001-05 v3.0.0 IOP001-05 v3.0.5 TIC-RT001-05 v3.0.5			
AL	TTR001-09 v2.0.0 IOP001-09 v1.1.0 TIC-RT001-09 v1.2.2			
E2EE	TTR001-10 v2.0.0 IOP001-10 v1.1.0 TIC-RT001-10 v1.2.2			
AIE	TTR001-11 v3.0.3 IOP001-11 v3.0.2 TIC-RT001-11 v3.2.5			

# Feature compliance report

Test Session	Rohill Hoogeveen November 2014			
<b>Core</b>				
Registration	Spot 0_pass_of_4			
ITSI attach	Spot 0_pass_of_1			
SwMI initiated location updating	Not Supported			
LA timer based Periodic location updating	Spot 0_pass_of_2			
De-registration	Spot 0_pass_of_1			
Group Management	PASSED Spot 1_pass_of_11			
Single group attachment	Spot 0_pass_of_5			
Multiple group attachment	Spot 0_pass_of_4			
MS initiated group detachment	PASSED Spot 1_pass_of_2			
SwMI initiated group management	Not Supported			
Group call	PASSED Spot 2_pass_of_11			
Normal group call	Spot 0_pass_of_4			
Late entry	Spot 0_pass_of_1			
Priority Group scanning	PASSED Spot 1_pass_of_3			
Call setup modifications	Spot 0_pass_of_1			
Resource Queuing based on Call Priority	PASSED Spot 1_pass_of_2			
Broadcast Call	Not Supported			



Limited coverage notification	Not Supported			
Individual call	PASSED Spot 2_pass_of_10			
Simplex individual call	PASSED Spot 1_pass_of_4			
Duplex individual call	PASSED Spot 1_pass_of_2			
Call setup modifications	Not Supported			
Resource Queuing based on Call Priority	Spot 0_pass_of_4			
Indication of imminent call disconnection	Not Supported			
Status messages	Spot 0_pass_of_4			
Individual addressed Status transfer	Spot 0_pass_of_1			
Group addressed Status transfer	Spot 0_pass_of_3			
Pre-emptive Priority Call	PASSED Spot 1_pass_of_6			
Pre-emption of Resources	PASSED Spot 1_pass_of_2			
Pre-emption of Busy Users	Spot 0_pass_of_4			
Emergency Call	PASSED Spot 1_pass_of_5			
Pre-emption of Resources	PASSED Spot 1_pass_of_2			
Pre-emption of Busy Users	Spot 0_pass_of_1			
Call setup modifications	Spot 0_pass_of_2			
Call disconnection by non-call owner	Not Supported			
Cell Re-selection	PASSED Spot 8_pass_of_16			
Undeclared	Spot 0_pass_of_1			
Unannounced	Spot 0_pass_of_3			
Announced - with Call Restoration	PASSED Spot 8_pass_of_12			
Announced - without Call Restoration	Not Supported			

Expedited	Not Supported			
PSTN interconnect	PASSED Spot 1_pass_of_6			
TETRA Originated Call	PASSED Spot 1_pass_of_2			
PSTN Originated Call	Spot 0_pass_of_1			
DTMF over-dial	Spot 0_pass_of_1			
Emergency Telephone Calls	Spot 0_pass_of_2			
MS-ISDN Numbering	Spot 0_pass_of_4			
MS ISDN - Voice Call	Spot 0_pass_of_2			
MS-ISDN Status	Spot 0_pass_of_2			
In Call Signalling	Spot 0_pass_of_8			
Slow Signalling on Traffic Channel (SACCH)	Spot 0_pass_of_4			
Fast Signalling on Traffic Channel (FACCH)	Spot 0_pass_of_4			
Subscriber Class Procedures	PASSED Spot 3_pass_of_9			
Cell Selection based on Subscriber Class	PASSED Spot 2_pass_of_3			
Subscriber Class Delivery during Location Update	Spot 0_pass_of_3			
Use of Preferred Subscriber Classes	PASSED Spot 1_pass_of_3			
Common Secondary Control Channels	PASSED Spot 2_pass_of_6			
One C-SCCH per cell	PASSED Spot 2_pass_of_3			
Two C-SCCH per cell	PASSED Spot 1_pass_of_3			
Three C-SCCH per cell	Spot 0_pass_of_2			
BS Fallback Operation	PASSED Spot 4_pass_of_13			
Switch to/from BS Fallback Operation	Spot 0_pass_of_2			
Roaming with BS Fallback Operation	PASSED Complete 2_pass_of_2			

Services with BS Fallback Operation	PASSED Spot 2_pass_of_8			
Ignore a cell in Fallback Operation	Spot 0_pass_of_1			
User selectable Fallback behaviour	Not Supported			
Energy Economy Mode				
Energy Economy Mode Operation	Not Supported			
Transmit Inhibit	PASSED Spot 1_pass_of_5			
TXI Activation & De-Activation	PASSED Spot 1_pass_of_4			
TXI Activation & De-Activation with TxI Status available to the Dispatcher	Not Supported			
Receipt of group addressed service during TXI	Spot 0_pass_of_1			
Mixed band operation				
Mixed band operation, inter-cell	Not Supported			
Mixed band operation, intra-cell	Not Supported			
Mixed band operation, Full	Not Supported			
<b>Short Data Service (SDS)</b>				
SDS Type 1, 2 or 3				
SDS Type 1	Not Supported			
SDS Type 2	Not Supported			
SDS Type 3	Not Supported			
SDS-TL	PASSED Spot 2_pass_of_7			
Individually Addressed	Spot 0_pass_of_1			
Group Addressed	Spot 0_pass_of_2			
Using MS-ISDN dialling	PASSED Spot 1_pass_of_2			
Using UCS2 coding scheme	PASSED Spot 1_pass_of_2			

Using 7-bit coding scheme	PASSED Complete 1_pass_of_1			
Using 8-bit Latin 1 coding scheme	Spot 0_pass_of_1			
Using 8-bit Latin 5 coding scheme	Complete			
Using 8-bit Latin 9 coding scheme	Complete			
Store and Forward				
Individually Addressed	Not Supported			
Group Addressed	Not Supported			
<b>Dynamic Group Number Assignment (DGNA)</b>				
Support for individually addressed DGNA	PASSED Spot 2_pass_of_12			
Support for individually addressed DGNA assignment without attachment	Spot 0_pass_of_3			
Support for individually addressed DGNA assignment with attachment as selected group	PASSED Spot 2_pass_of_3			
Support for individually addressed DGNA assignment with attachment as scanned group	Spot 0_pass_of_4			
Support for individually addressed DGNA assignment with rejected attachment	Not Supported			
Support for individually addressed assignment for pre-programmed group	Spot 0_pass_of_5			
Support for group addressed DGNA	PASSED Spot 2_pass_of_3			
Support for group addressed DGNA assignment	PASSED Spot 1_pass_of_2			

Management of 'group assignment lifetime'	Not Supported			
Support for group addressed DGNA deassignment	PASSED Complete 1_pass_of_1			
Tolerance of unsupported DGNA functions				
MS tolerance of unsupported individual addressed DGNA signalling	Not Supported			
MS tolerance of unsupported group addressed DGNA signalling	Not Supported			
<b>Authentication</b>				
SwMI Initiated (non-mutual) Authentication	Spot 0_pass_of_3			
Attach with authentication	Spot 0_pass_of_1			
Roaming with authentication	Spot 0_pass_of_1			
SwMI rejects MS during authentication	Spot 0_pass_of_1			
MS rejects SwMI during authentication	Not Supported			
SwMI Initiated Authentication made Mutual by MS	PASSED Spot 1_pass_of_2			
Attach with authentication	Spot 0_pass_of_1			
Roaming with authentication	PASSED Complete 1_pass_of_1			
TEI Query				
TEI Query Operation	Not Supported			

Packet Data				
Context Management	PASSED Spot 2_pass_of_11			
Context Activation	PASSED Spot 2_pass_of_7			
User authentication	Spot 0_pass_of_4			
Single Slot Packet Data	PASSED Spot 3_pass_of_9			
Data Transfer	PASSED Spot 1_pass_of_6			
Cell re-selection	PASSED Spot 2_pass_of_3			
Multi Slot Packet Data	PASSED Spot 1_pass_of_4			
Data Transfer	PASSED Spot 1_pass_of_4			
<b>TEDS</b>				
TEDS with Context Activation	Not Supported			
TEDS Data Transmission, using LLC Optimisation	Not Supported			
TEDS Data Transmission, not using LLC Optimisation	Not Supported			
TEDS Cell Reselection, using LLC Optimisation	Not Supported			
TEDS Cell Reselection, not using LLC Optimisation	Not Supported			
<b>Mixed band operation</b>				
Mixed band operation, inter-cell	Not Supported			
Mixed band operation, intra-cell	Not Supported			
Mixed band operation, Full	Not Supported			

TETRA Ambience Listening (SS-AL)				
Ambience Listening	PASSED Spot 1_pass_of_5			
SS-AL Call Setup	Spot 0_pass_of_2			
MS initiated SS-AL disconnection	PASSED Spot 1_pass_of_3			
No Indication to affected user	PASSED Spot 1_pass_of_5			
Interaction with Transmit Inhibit	PASSED Spot 1_pass_of_2			
AL can override TxI	PASSED Complete 1_pass_of_1			
AL cannot override TxI	Spot 0_pass_of_1			
End to End Encryption				
E2EE Voice Call	PASSED Spot 2_pass_of_10			
Individual (P2P) call	PASSED Spot 1_pass_of_4			
Group (P2MP) call	PASSED Spot 1_pass_of_2			
Clear Voice Override (CVO): Acceptance	Spot 0_pass_of_1			
Clear Voice Override (CVO): User Initiated	Spot 0_pass_of_2			
Clear Voice Override (CVO): Automatic	Spot 0_pass_of_1			

Air Interface Encryption				
Security Class 2 Air Interface Encryption	PASSED Spot 5_pass_of_12			
Location Updating and AI Signalling Protection	PASSED Spot 2_pass_of_3			
TM-SCK provisioning during location updating	Not Supported			
Communications between parties using encryption	PASSED Complete 2_pass_of_2			
Communications between clear and encrypted parties	Spot 0_pass_of_3			
Communications between encrypted parties on a channel designated to operate in clear	Spot 0_pass_of_2			
OTAR of TM-SCK	Not Supported			
Change of TM-SCK	Not Supported			
Packet Data with Class 2 Air Interface Encryption	PASSED Spot 1_pass_of_2			
Security Class 3 Air Interface Encryption	PASSED Spot 3_pass_of_17			
Clear Location Updating and AI Signalling Protection	Spot 0_pass_of_3			
Encrypted Location Updating and AI Signalling Protection	PASSED Spot 2_pass_of_5			
DCK Forwarding at MS request	Not Supported			
DCK Forwarding by SwMI (without MS request)	Not Supported			
DCK Retrieval	PASSED Spot 2_pass_of_5			
CCK provisioning during location updating	PASSED Spot 1_pass_of_5			
Communications between parties using encryption	Spot 0_pass_of_2			



Communications between clear and encrypted parties	Spot 0_pass_of_3			
Communications between encrypted parties on a channel designated to operate in clear	Spot 0_pass_of_2			
OTAR of CCK	Not Supported			
Change of CCK	Not Supported			
Packet Data with Class 3 Air Interface Encryption	PASSED Spot 1_pass_of_2			
Security Class 3G Air Interface Encryption				
GCK Key Association setting	Not Supported			
Communications between parties using encryption	Not Supported			
Communications between clear and encrypted parties	Not Supported			
OTAR of GCK	Not Supported			
Change of GCK	Not Supported			
Management of CMG and GSKO				
OTAR and change of CMG and GSKO	Not Supported			
Key Status demand				
SCK Key Status demand	Not Supported			
GCK Key Status demand	Not Supported			
GSKO Key Status demand	Not Supported			
Change of Security Class for Fallback operation				
Seamless change to Security Class 2 for BS Fallback operation	Not Supported			

Non-seamless change to Security Class 2 for BS Fallback operation	Not Supported			
Provisioning of TM-SCK for fallback to Security Class 2 operation	Not Supported			
Change to Security Class 1 for BS Fallback operation	Not Supported			
Change of Security Class (other than for Fallback operation)				
Change between Security Class 3 and Security Class 3G	Not Supported			
Change between Security Class 2 and Security Class 3	Not Supported			
Change from Security Class 3G to Security Class 2	Not Supported			
Key Management for Secure Direct Mode Operation				
OTAR of DM-SCK	Not Supported			
Change of DM-SCK	Not Supported			