

TETRA Interoperability Certificate

**Motorola Solutions, Dimetra IP R8.2, SwMI –
Teltronic, TRM-300, Terminal**

Krakow, April 2014

Latest Certified SwMI SW Release:	8.2	Latest Certified Terminal SW Release:	v11
Latest Certified SwMI HW Release:	Dimetra IP R8.2	Latest Certified Terminal HW Release:	CCP 30.03

ISCTI (Istituto Superiore delle Comunicazioni e delle Tecnologie dell'Informazione) certifies, that the Motorola Solutions, Dimetra IP R8.2, SwMI and the Teltronic, TRM-300, terminal have been subject to interoperability testing for the “certified” features listed on second page of this certificate, in accordance with the TETRA Interoperability Profiles, TIP compliance Test Plan and related TETRA interoperability requirement tables.

The table lists all the available TETRA interoperability profiles, and summarizes the main functionalities of every profile according to the TETRA interoperability requirement tables.

A feature is “Certified” when it has been successfully tested during the last test session with one of the testing method described in the TETRA process document part 1 (TPD001-01).

A breakdown into the feature details is given in the Feature Compliance Overview section of this certificate.

This certificate has been issued following a fully witnessed multi test session between Motorola Solutions and Teltronic on April 2014. Detailed test results are listed in the Test Report associated to this Certificate. Details and explanation about the procedure used to provide verdicts are in the TIC process TPD001-01.

IOP test engineer



Massimo Proietti

Radio Office Manager

Giuseppe Pierri



ISCTI - V.le America 201, 00144 Rome, Italy
Ph.: +39 06 5444 2663, Fax: +39 06 5410904
e-mail: tetra_ctc.iscom@mise.gov.it
Web: www.mise.gov.it

Date of issue
22 October 2014
v 2

Certified features

Tetra Association TTR001-01:Core	
Registration	Certified
Group Management	Certified
Group call	-
Individual call	-
Status messages	Certified
Pre-emptive Priority Call	-
Emergency Call	-
Cell Re-selection	Certified
PSTN interconnect	-
MS-ISDN Numbering	-
In Call Signalling	-
Subscriber Class Procedures	Certified
Common Secondary Control Channels	Certified
BS Fallback Operation	Certified
Energy Economy Mode	-
Transmit Inhibit	Certified
Mixed band operation	Certified
Tetra Association TTR001-02:SDS	
SDS Type 1, 2 or 3	-
SDS-TL	Certified
Store and Forward	-
Tetra Association TTR001-03:DGNA	
Support for individually addressed DGNA	Certified

Support for group addressed DGNA	-
Tolerance of unsupported DGNA functions	-

Tetra Association TTR001-04:Auth	
SwMI Initiated (non-mutual) Authentication	Certified
SwMI Initiated Authentication made Mutual by MS	Certified
TEI Query	-
Tetra Association TTR001-05:PD	
Context Management	Certified
Single Slot Packet Data	Certified
Multi Slot Packet Data	Certified
TEDS	-
Mixed band operation	Certified
Tetra Association TTR001-11:AIE	
Security Class 2 Air Interface Encryption	Certified
Security Class 3 Air Interface Encryption	Certified
Security Class 3G Air Interface Encryption	-
Change of CMG and GSKO	-
Key Status demand	-
Change of Security Class for Fallback operation	-
Change of Security Class (other than for Fallback operation)	-
Key Management for Secure Direct Mode Operation	-
Tetra Association TTR001-13:ED	
Enable and temporary disable of an MS	Certified
Permanent disable of an MS	Certified

Tetra Association TTR001-14:TKD	
Delivery of Authentication Data	Certified
Delivery of SCK	Certified
Delivery method	Certified
Tetra Association TTR001-19:LIP	
Location Information Protocol	Certified

Feature Compliance Overview

The first pages of this certificate provide an indication about the main interoperable TETRA features for each TIP specification (as described in the TIC-RT). The main interoperable TETRA features result depend on a set of sub-feature, the outcomes associated to each sub-feature are directly derived from the analysis of the performed test cases.

The results associated to each feature and sub-feature are shown in the "Feature compliance report" table below. The main features are indicated with grey background and the associated sub-features (or second level features) have light blue background.

The outcome assigned to a sub-feature as shown on page 2, is derived by the Feature compliance report tables.

Outcome	Definition
Certified	All required tests have been performed and passed
Partial	Not all the required tests have been performed but none have failed
-	Feature cannot be certified e.g. it is not supported by at least one product, no tests were performed, or some tests were performed but at least one failed

The outcome is derived from the verdict assigned to a sub feature which is the result of an analysis of the test case results listed in the Test Report. The verdict assigned to each sub-feature is derived from one or several test case results or test steps result, the TETRA Interoperability requirement tables (TIC-RTs) indicate the link between sub-features and test cases for the certified set of equipment capabilities (see Test Report).

Verdict	Definition
Passed	All mandated tests or steps of tests linked to this functionality (as per TIC-RT indication) are compliant with the TIP specification relevant to this feature.
Incomplete	Not all Mandated tests (as per TIC-RT indication) have been executed
Failed	At least one of mandated test or steps of tests linked to this functionality failed to match the TIP specification relevant to this feature.

The verdict associated to the feature gives also indication about the method used to test that feature.

The allowed testing Methods are listed in the table below, a complete description of the procedures and constraints associated to each of them can be found in the "TPD001-01 TETRA Interoperability Certification Process Description" document.

Testing Method	Description
Complete	All mandated tests associated to the feature have been executed
Spot	Only a selection of the mandatory test cases associated to the feature has been executed during the test session. These tests are a subset of the tests performed on an equivalent software which has been "completely" tested against the same functionality on a different equipment, see manufacturer declaration in the associated Test Report
Spot	Only a selection of the mandatory test cases associated to the feature has been executed during the test session. These tests are a subset of the tests performed on a previous version of the same software which has been "completely" tested in a previous test session against the same functionality, see manufacturer definition in the associated Test Report
Spot on spot	The Spot method has been applied on the verdicts based on the spot testing method
Witnessed	The TIP heading lines in the Feature Compliance Report indicate whether each TIP is partially or fully witnessed by the Certification Body. Additionally, for a partially-witnessed TIP, the number of witnessed test cases that passed is shown for each the feature and sub-feature. There may have been some un-witnessed passed tests and they will have been found to be successful based on the log file evaluation.

Depending on equipment capabilities declared by the manufacturer, some features or sub features cannot be tested. The following table describes meaning of the used abbreviation:

Indication	Definition
Not supported	The SwMI and/or MS do not support the minimum features required to verify these items

ISCTI has made every effort to ensure that every result has been correctly evaluated in accordance

with the relevant TIPs, Test Plans and TIC-RTs. ISCTI has no liability for the test results, or towards the manufacturers.

The table on the following page lists HW and SW releases of SwMI and Terminal under test in the last four test sessions and the used TIP specifications, Test Plans and TIC-RTs.

This Certificate and Certificates from previous test sessions are available on the TETRA + Critical Communications Association web site (<http://www.tandcca.com/interop/page/12476>).

The feature results are shown in the tables below.

Information on equipment under test and document references

Test Session Date/Place	Motorola Solutions Krakow April 2014			
SwMI Type	Dimetra IP R8.2			
SwMI HW Release	Dimetra IP R8.2			
SwMI SW Release	8,2			
Terminal Type	TRM-300			
Terminal HW Release	CCP 30.03			
Terminal SW Release	v11			
TIP Specs and TIP Compliance Test Plans				
Core	TTR001-01 v6.0.0 IOP001-01 v3.0.0 TIC-RT001-01 v260			

SDS	TTR001-02 v2.1.1 IOP001-02 v2.0.0 TIC-RT001-02 v213			
DGNA	TTR001-03 v2.0.0 IOP001-03 v2.0.1 TIC-RT001-03 v222			
Auth	TTR001-04 v3.0.0 IOP001-04 v2.0.0 TIC-RT001-04 v223			
PD	TTR001-05 v3.0.0 IOP001-05 v3.0.5 TIC-RT001-05 v305			
AIE	TTR001-11 v3.0.3 IOP001-11 v3.0.2 TIC-RT001-11 v325			
ED	TTR001-13 v2.0.0 IOP001-13 v1.0.0 TIC-RT001-13 v146			
TKD	TTR001-14 v1.0.3 IOP001-14 v1.0.0 TIC-RT001-14 v117			
LIP	TTR001-19 v1.0.0 IOP001-19 v1.0.0 TIC-RT001-19 v105			

Feature compliance report

Test Session	Motorola Solutions Krakow April 2014			
Core				
Registration	Spot 0_pass_of_3			
ITSI attach	Spot 0_pass_of_1			
SwMI initiated location updating	Spot 0_pass_of_1			
LA timer based Periodic location updating	Not Supported			
De-registration	Spot 0_pass_of_1			
Group Management	PASSED Spot 1_pass_of_8			
Single group attachment	Spot 0_pass_of_2			
Multiple group attachment	PASSED Spot 1_pass_of_4			
MS initiated group detachment	Spot 0_pass_of_2			
SwMI initiated group management	Not Supported			
Group call				
Normal group call	Not Supported			
Late entry	Not Supported			
Priority Group scanning	Not Supported			
Call setup modifications	Not Supported			
Resource Queuing based on Call Priority	Not Supported			
Broadcast Call	Not Supported			

Limited coverage notification	Not Supported			
Individual call	Not Supported			
Simplex individual call	Not Supported			
Duplex individual call	Not Supported			
Call setup modifications	Not Supported			
Resource Queuing based on Call Priority	Not Supported			
Indication of imminent call disconnection	Not Supported			
Status messages	Spot 0_pass_of_1			
Individual addressed Status transfer	Not Supported			
Group addressed Status transfer	Spot 0_pass_of_1			
Pre-emptive Priority Call				
Pre-emption of Resources	Not Supported			
Pre-emption of Busy Users	Not Supported			
Emergency Call				
Pre-emption of Resources	Not Supported			
Pre-emption of Busy Users	Not Supported			
Call setup modifications	Not Supported			
Call disconnection by non-call owner	Not Supported			
Cell Re-selection	PASSED Complete 1_pass_of_1			
Undeclared	PASSED Complete 1_pass_of_1			
Unannounced	Not Supported			
Announced - with Call Restoration	Not Supported			
Announced - without Call Restoration	Not Supported			

Expedited	Not Supported			
PSTN interconnect				
TETRA Originated Call	Not Supported			
PSTN Originated Call	Not Supported			
DTMF over-dial	Not Supported			
Emergency Telephone Calls	Not Supported			
MS-ISDN Numbering				
MS ISDN - Voice Call	Not Supported			
MS-ISDN Status	Not Supported			
In Call Signalling				
Slow Signalling on Traffic Channel (SACCH)	Not Supported			
Fast Signalling on Traffic Channel (FACCH)	Not Supported			
Subscriber Class Procedures	PASSED Spot 1_pass_of_4			
Cell Selection based on Subscriber Class	Spot 0_pass_of_1			
Subscriber Class Delivery during Location Update	Not Supported			
Use of Preferred Subscriber Classes	PASSED Spot 1_pass_of_3			
Common Secondary Control Channels	PASSED Spot 1_pass_of_7			
One C-SCCH per cell	Spot 0_pass_of_4			
Two C-SCCH per cell	PASSED Spot 1_pass_of_3			
Three C-SCCH per cell	Spot 0_pass_of_2			
BS Fallback Operation	PASSED Spot 2_pass_of_5			
Switch to/from BS Fallback Operation	PASSED Spot 1_pass_of_2			
Roaming with BS Fallback Operation	PASSED Spot 1_pass_of_2			

Services with BS Fallback Operation	Spot 0_pass_of_1			
Energy Economy Mode				
Energy Economy Mode Operation	Not Supported			
Transmit Inhibit	PASSED Spot 2_pass_of_7			
TXI Activation & De-Activation	PASSED Spot 1_pass_of_3			
TXI Activation & De-Activation with TxI Status available to the Dispatcher	PASSED Spot 1_pass_of_3			
Receipt of group addressed service during TXI	Spot 0_pass_of_1			
Mixed band operation	PASSED Complete 1_pass_of_1			
Mixed band operation, inter-cell	PASSED Complete 1_pass_of_1			
Mixed band operation, intra-cell	Not Supported			
Mixed band operation, Full	Not Supported			
SDS Type 1, 2 or 3				
SDS Type 1	Not Supported			
SDS Type 2	Not Supported			
SDS Type 3	Not Supported			
SDS-TL	PASSED Spot 1_pass_of_5			
Individually Addressed	Spot 0_pass_of_1			
Group Addressed	PASSED Spot 1_pass_of_2			
Using MS-ISDN dialling	Not Supported			
Using UCS2 coding scheme	Spot 0_pass_of_2			
Using 7-bit coding scheme	Not Supported			
Using 8-bit Latin 1 coding scheme	Spot 0_pass_of_1			

Using 8-bit Latin 5 coding scheme	Spot 0_pass_of_1			
Using 8-bit Latin 9 coding scheme	Not Supported			
Store and Forward				
Individually Addressed	Not Supported			
Group Addressed	Not Supported			
Dynamic Group Number Assignment (DGNA)				
Support for individually addressed DGNA	PASSED Spot 1_pass_of_2			
Support for individually addressed DGNA assignment without attachment	PASSED Spot 1_pass_of_2			
Support for individually addressed DGNA assignment with attachment as selected group	Not Supported			
Support for individually addressed DGNA assignment with attachment as scanned group	Not Supported			
Support for individually addressed DGNA assignment with rejected attachment	Not Supported			
Support for individually addressed assignment for pre-programmed group	Not Supported			
Support for group addressed DGNA				
Support for group addressed DGNA assignment	Not Supported			
Management of 'group assignment lifetime'	Not Supported			

Support for group addressed DGNA deassignment	Not Supported			
Tolerance of unsupported DGNA functions				
MS tolerance of unsupported individual addressed DGNA signalling	Not Supported			
MS tolerance of unsupported group addressed DGNA signalling	Not Supported			
Authentication				
SwMI Initiated (non-mutual) Authentication	PASSED Spot 1_pass_of_3			
Attach with authentication	Spot 0_pass_of_1			
Roaming with authentication	Spot 0_pass_of_1			
SwMI rejects MS during authentication	PASSED Complete 1_pass_of_1			
MS rejects SwMI during authentication	Not Supported			
SwMI Initiated Authentication made Mutual by MS	Spot 0_pass_of_2			
Attach with authentication	Spot 0_pass_of_1			
Roaming with authentication	Spot 0_pass_of_1			
TEI Query				
TEI Query Operation	Not Supported			

Packet Data				
Context Management	PASSED Spot 2_pass_of_9			
Context Activation	PASSED Spot 1_pass_of_7			
User authentication	PASSED Spot 1_pass_of_2			
Single Slot Packet Data	PASSED Spot 2_pass_of_10			
Data Transfer	PASSED Spot 1_pass_of_7			
Cell re-selection	PASSED Spot 1_pass_of_3			
Multi Slot Packet Data	Spot 0_pass_of_2			
Data Transfer	Spot 0_pass_of_2			
TEDS				
TEDS with Context Activation	Not Supported			
TEDS Data Transmission, using LLC Optimisation	Not Supported			
TEDS Data Transmission, not using LLC Optimisation	Not Supported			
TEDS Cell Reselection, using LLC Optimisation	Not Supported			
TEDS Cell Reselection, not using LLC Optimisation	Not Supported			
Mixed band operation	PASSED Spot 1_pass_of_2			
Mixed band operation, inter-cell	PASSED Spot 1_pass_of_2			
Mixed band operation, intra-cell	PASSED Spot 1_pass_of_2			
Mixed band operation, Full	PASSED Spot 1_pass_of_2			

Air Interface Encryption				
Security Class 2 Air Interface Encryption	PASSED Spot 2_pass_of_6			
Location Updating and AI Signalling Protection	PASSED Spot 1_pass_of_2			
TM-SCK provisioning during location updating	Not Supported			
Communications between parties using encryption	Not Supported			
Communications between clear and encrypted parties	Not Supported			
Communications between encrypted parties on a channel designated to operate in clear	Not Supported			
OTAR of TM-SCK	Not Supported			
Change of TM-SCK	PASSED Spot 1_pass_of_2			
Packet Data with Class 2 Air Interface Encryption	Spot 0_pass_of_2			
Security Class 3 Air Interface Encryption	PASSED Spot 1_pass_of_7			
Clear Location Updating and AI Signalling Protection	Spot 0_pass_of_2			
Encrypted Location Updating and AI Signalling Protection	PASSED Spot 1_pass_of_2			
DCK Forwarding at MS request	Not Supported			
DCK Forwarding by SwMI (without MS request)	Not Supported			
DCK Retrieval	PASSED Spot 1_pass_of_2			
CCK provisioning during location updating	PASSED Spot 1_pass_of_3			

Communications between parties using encryption	Not Supported			
Communications between clear and encrypted parties	Not Supported			
Communications between encrypted parties on a channel designated to operate in clear	Not Supported			
OTAR of CCK	Not Supported			
Change of CCK	Spot 0_pass_of_1			
Packet Data with Class 3 Air Interface Encryption	Spot 0_pass_of_2			
Security Class 3G Air Interface Encryption				
GCK Key Association setting	Not Supported			
Communications between parties using encryption	Not Supported			
Communications between clear and encrypted parties	Not Supported			
OTAR of GCK	Not Supported			
Change of GCK	Not Supported			
Management of CMG and GSKO				
OTAR and change of CMG and GSKO	Not Supported			
Key Status demand				
SCK Key Status demand	Not Supported			
GCK Key Status demand	Not Supported			
GSKO Key Status demand	Not Supported			
Change of Security Class for Fallback operation				

Seamless change to Security Class 2 for BS Fallback operation	Not Supported			
Non-seamless change to Security Class 2 for BS Fallback operation	Not Supported			
Provisioning of TM-SCK for fallback to Security Class 2 operation	Not Supported			
Change to Security Class 1 for BS Fallback operation	Not Supported			
Change of Security Class (other than for Fallback operation)				
Change between Security Class 3 and Security Class 3G	Not Supported			
Change between Security Class 2 and Security Class 3	Not Supported			
Change from Security Class 3G to Security Class 2	Not Supported			
Key Management for Secure Direct Mode Operation				
OTAR of DM-SCK	Not Supported			
Change of DM-SCK	Not Supported			

Enable Disable				
Enable and temporary disable of an MS	PASSED Spot 1_pass_of_5			
Enable and temporary disable of an MS without authentication	PASSED Spot 1_pass_of_2			
Enable and temporary disable of an MS with authentication	Not Supported			
Registration of a temporary	Spot 0_pass_of_2			

disabled MS				
Rejection of applicable invalid enable/disable requests	Not Supported			
Removable SIMs do not affect the subscriber or equipment that has been enabled/disabled	Not Supported			
Disabling of an MS during a call or while on the PDCH	Spot 0_pass_of_1			
Permanent disable of an MS	PASSED Spot 1_pass_of_2			
Permanent disable of an MS with authentication	Spot 0_pass_of_1			
Permanently Disabled MS cannot send air interface signalling	PASSED Complete 1_pass_of_1			
Key Delivery				
Delivery of Authentication Data	PASSED Spot 1_pass_of_2			
Authentication Key Delivery	PASSED Complete 1_pass_of_1			
ITSI Delivery	Spot 0_pass_of_1			
Delivery of SCK	Spot 0_pass_of_1			
SCK Delivery to SCK delivery	Not Supported			
SCK Delivery to SwMI	Spot 0_pass_of_1			
SCK Delivery to SCK loading	Not Supported			
Delivery method	PASSED Spot 1_pass_of_3			
Plain text on physical media	PASSED Spot 1_pass_of_3			
Encrypted text on physical	Not Supported			

media				
Electronic transfer	Not Supported			
LIP				
Location Information Protocol	PASSED Spot 1_pass_of_5			
LIP over SDS	PASSED Spot 1_pass_of_3			
LIP over Packet Data	Not Supported			
Time based reporting	PASSED Spot 1_pass_of_2			
Distance based reporting - NOT TESTABLE	Not Supported			
Reporting using Long reports	Not Supported			
Reporting Enable & Disable	Not Supported			
Temporary reporting control	Not Supported			
Trigger modification	Not Supported			
Immediate Location Reporting	Spot 0_pass_of_1			
Reporting Lifetimes	Not Supported			
Error Reporting	Spot 0_pass_of_1			

Annex A

Annex A

List of Revisions of the Certificate

Date	Ver.	Modification
8 October 2014	1	First published version
22 October 2014	2	updating: on "Feature Compliant Report" table all the "Regression" became "Spot"

IOP test engineer



Ivano Luciani

Radio Office Manager

Giuseppe Pierri

