



IST doc.10 rev.1

TETRA Terminal Interoperability Certificate

November 2004

MOTOROLA



Manufacturer	Type	Software/Hardware Release No.	Period of testing
Motorola	MTH800	SW: R07.020.5154 HW: FUE1054A	17-18 November 2004

ISCTI (Istituto Superiore delle Comunicazioni e delle Tecnologie dell'Informazione) has witnessed that the Motorola Terminal is operating in accordance with:

TETRA Interoperability Profile:

TETRA MoU, TTR001-01, Core, Ver. 3.0.13, June 2001
TETRA MoU, TTR001-02, SDS, Ver. 1.0.1, August 2001
TETRA MoU, TTR001-03, DGNA, Ver. 1.0.3, May 2001
TETRA MoU, TTR001-04, Authentication, Ver. 1.0.0, November 2000
TETRA MoU, TTR001-05, Packet Data, Ver. 1.0.0, November 2000
TETRA MoU, TTR001-09, Ambience Listening, Ver. 1.0.3, January 2002
TETRA MoU, TTR001-11, Air Interface Encryption, Ver. 1.0.0, December 2001

The test results for the tested features can be found in the tables of this certificate.


Authorized IOP test engineer
(Ilyano Luciani)
(Massimo Lucenti)


Radio Office Manager
(Ing. A. La Padula)


01 MAR. 2005

Test Session: Lab Motorola, Berlin, November 2004
Equipment: Motorola, MTH800 Terminal

ISCTI - V.le America 201, 00144 Rome, Italy
Ph.: +39 06 5444 2663, Fax: +39 06 5410904



Information on the equipments used for testing in the November 2004 IOP Test Session

The tests were performed using the following SwMI:

Manufacturer	Type	Software/Hardware Release No.
Motorola	Dimetra IP R5.2	ZC SW: ZCTE-R05.02.08.02 NM SW: R13.01.00.03 EBTS SW TSC: R05.32.29 BRC: R05.22.41 (TEA2)

Additional information about the test performed

The tests were performed in the LA1 and LA2 sites. The SwMI was operating with the following configuration:

MCC	262
MNC	5003
Colour code	1 (LA7) and 2 (LA8)
LA1 carrier frequency (BS Tx)	394,76255 MHz
LA2 carrier frequency (BS Tx)	394,5625 MHz
PSTN gateway SSI	16777184
Subscriber classes	FFFF ₁₆

Note: TIP compliance testing focuses on functionality on the OSI model layers two, three and higher and therefore is frequency band independent.



IOP Test Plans used for testing

The following Test Plans were used in the Test Session:

TETRA MoU, IOP001-01, Core, Ver. 1.1.0

TETRA MoU, IOP001-02, SDS, Ver. 1.1.0

TETRA MoU, IOP001-03, DGNA, Ver. 1.1.0

TETRA MoU, IOP001-04, Authentication, Ver. 1.1.0

TETRA MoU, IOP001-05, Packet Data, Ver. 1.1.0

TETRA MoU, IOP001-09, Ambience Listening, Ver. 1.1.0

TETRA MoU, IOP001-11, Air Interface Encryption, Ver. 1.1.0

Test Results

The test results are shown in the tables below.

Test results and the certificates from previous IOP test session are available on TETRA MoU web site (<http://www.tetramou.com>).

Tables indicate whether or not tests addressing a specific requirement of the TIP specification have been performed, whether or not the requirement is applicable for the SwMI, and the result of the test if executed. Each entry of the table may take one of seven values:

-	No test performed.
N/A	Not applicable for the SwMI
No	Not supported by Terminal
NTPA	No Test Plan/case Available
P	Pass
F	Fail
I	Inconclusive

The test results have been derived from examining the behaviour of a live system. The verdicts indicated are based on the log evaluation of the information exchange between the SwMI and the terminals indicated in the following tables. The verdicts reflect the fact that at the time of the IOP testing it was/was not possible to demonstrate a behaviour that was in accordance with the related requirement.

ISCTI has made every effort to ensure that tests are in accordance with the relevant TIPs. ISCTI has no liability for the test results, or towards the manufacturers.

Motorola SwMI			Motorola MTH800
TTR001-01	CORE		
TTR001-01 6	Registration		
TTR001-01 6.1	ITSI attach ITSI attach without group attachment – 1.1	IOP001-01 1.1	No
TTR001-01 6.2	ITSI attach including group attachment ITSI attach including group attachment – 1.2	IOP001-01 1.2	P
TTR001-01 6.2	ITSI attach including group attachment MS initiated Multiple group attachment during MS registration – 2.2.1	IOP001-01 2.2.1	P
TTR001-01 6.3	Roaming & periodic location updating Cell re-selection without communication activity – 7.1.1	IOP001-01 7.1.1	P
TTR001-01 6.4	SwMI initiated location updating SwMI initiated location updating without group reporting – 1.3.1	IOP001-01 1.3.1	Note 1
TTR001-01 6.4	SwMI initiated location updating SwMI initiated location updating with group reporting – 1.3.2	IOP001-01 1.3.2	N/A
TTR001-01 6.5	De-registration De-registration – 1.4	IOP001-01 1.4	P
TTR001-01 7	Individual call		
TTR001-01 7.1	Call set-up		
TTR001-01 7.1.1	Hook signalling Individual hook call set-up – 4.1.1	IOP001-01 4.1.1	P
TTR001-01 7.1.1	Hook signalling Individual call set-up, resource queuing – 4.1.3	IOP001-01 4.1.3	P
TTR001-01 7.1.1	Hook signalling Duplex call set-up – 4.2.1	IOP001-01 4.2.1	P
TTR001-01 7.1.1	Hook signalling Duplex call set-up, resource queuing – 4.2.2	IOP001-01 4.2.2	P
TTR001-01 7.1.1	Hook signalling MS-ISDN Individual call – 9.1	IOP001-01 9.1	N/A
TTR001-01 7.1.2	Direct through-connect Individual direct call set-up – 4.1.2	IOP001-01 4.1.2	N/A
TTR001-01 7.1.2	Direct through-connect Individual call set-up, resource queuing – 4.1.3	IOP001-01 4.1.3	N/A
TTR001-01 7.1.2	Direct through-connect MS-ISDN Individual call – 9.1	IOP001-01 9.1	N/A
TTR001-01 7.1.3	Call set-up Modifications		
TTR001-01 7.1.3.1.4	Point to point' to 'point to multipoint' Emergency call set-up, P2P to P2MP call modification – 6.2.2	IOP001-01 6.2.2	N/A
TTR001-01 7.1.3.2.1	Direct to hook Call set-up Modification by Called Party, Direct to Hook, Calling Party signalling – 4.3.1.1	IOP001-01 4.3.1.1	N/A
TTR001-01 7.1.3.2.1	Direct to hook Call set-up Modification by Called Party, Direct to Hook, Called Party signalling – 4.3.1.2	IOP001-01 4.3.1.2	N/A
TTR001-01 7.1.3.2.3	Duplex to simplex Call set-up Modification by Called Party, duplex to semi-duplex, Calling Party signalling – 4.3.2.1	IOP001-01 4.3.2.1	N/A
TTR001-01 7.1.3.2.3	Duplex to simplex Call set-up Modification by Called Party, duplex to semi-duplex, Called Party signalling – 4.3.2.2	IOP001-01 4.3.2.2	N/A
TTR001-01 7.2	Transmission control		
TTR001-01 7.2.1	End of transmission Individual hook call set-up – 4.1.1	IOP001-01 4.1.1	P
TTR001-01 7.2.1	End of transmission Individual direct call set-up – 4.1.2	IOP001-01 4.1.2	N/A
TTR001-01 7.2.2	Request to transmit Individual hook call set-up – 4.1.1	IOP001-01 4.1.1	P
TTR001-01 7.2.2	Request to transmit Individual direct call set-up – 4.1.2	IOP001-01 4.1.2	N/A
TTR001-01 7.2.2	Request to transmit MS-ISDN Individual call – 9.1	IOP001-01 9.1	N/A
TTR001-01 7.2.3	Request to transmit (in the presence of an active talker) Pre-emptive speech item request, non pre-emptive transmission request queuing – 4.1.4	IOP001-01 4.1.4	N/A
TTR001-01 7.2.3	Request to transmit (in the presence of an active talker) Pre-emptive speech item request, non pre-emptive transmission request rejection – 4.1.5	IOP001-01 4.1.5	P
TTR001-01 7.2.3	Request to transmit (in the presence of the an active talker) MS-ISDN Individual call – 9.1	IOP001-01 9.1	N/A
TTR001-01 7.3	Call Maintenance Queuing during Individual call restoration, Transmitting – 7.3.4.1	IOP001-01 7.3.4.1	N/A
TTR001-01 7.3	Call Maintenance Queuing during Individual call restoration, Receiving. (Announced Type 3) – 7.3.4.2	IOP001-01 7.3.4.2	N/A
TTR001-01 7.3	Call Maintenance Queuing during Individual call restoration, Receiving (Unannounced) – 7.3.4.3	IOP001-01 7.3.4.3	N/A

Motorola SwMI			Motorola MTH800
TTR001-01 7.3	Call Maintenance Queuing during Individual call restoration, Communication inactivity. (Announced Type 3) – 7.3.5.1	IOP001-01 7.3.5.1	N/A
TTR001-01 7.3	Call Maintenance Queuing during Individual call restoration, Communication inactivity (Unannounced) – 7.3.5.2	IOP001-01 7.3.5.2	N/A
TTR001-01 7.3	Call Maintenance Queuing during Duplex call restoration (Announced type 3) – 7.4.2	IOP001-01 7.4.2	N/A
TTR001-01 7.4	Call disconnection Individual hook call set-up – 4.1.1	IOP001-01 4.1.1	P
TTR001-01 7.4	Call disconnection Individual direct call set-up – 4.1.2	IOP001-01 4.1.2	N/A
TTR001-01 7.4	Call disconnection Duplex call set-up – 4.2.1	IOP001-01 4.2.1	P
TTR001-01 7.5	Emergency individual call Emergency individual call. Resource pre-emption – 6.2.1	IOP001-01 6.2.1	N/A
TTR001-01 7.5.1	Emergency speech item request Emergency individual call. Resource pre-emption – 6.2.1	IOP001-01 6.2.1	N/A
TTR001-01 7.5.2	Emergency individual call modification Emergency call set-up, P2P to P2MP call modification – 6.2.2	IOP001-01 6.2.2	N/A
TTR001-01 7.6	Pre-emptive Priority Individual Call Pre-emptive priority individual call, resource pre-emption – 4.1.6	IOP001-01 4.1.6	-
TTR001-01 7.6	Pre-emptive Priority Individual Call Pre-emptive priority individual call to user in individual call – accepted by MS – 4.1.7	IOP001-01 4.1.7	P
TTR001-01 8	Group management		
TTR001-01 8.1	General Requirements Status to scanned group – 5.1.2.3	IOP001-01 5.1.2.3	N/A
TTR001-01 8.2.5	Class of usage values 101₂, 011₂, 010₂, High, normal, low priority scanned Status to scanned group – 5.1.2.3	IOP001-01 5.1.2.3	N/A
TTR001-01 8.2.7	Selected group and SwMI initiated attachment/detachments SwMI initiated Temporary 1 group detachment and re-attachment of selected group – 2.4.2	IOP001-01 2.4.2	N/A
TTR001-01 8.2.7	Selected group and SwMI initiated attachment/detachments SwMI initiated Temporary 1 group detachment and re-attachment of the non-selected group – 2.4.3	IOP001-01 2.4.3	N/A
TTR001-01 8.4	Attachment of the selected group MS initiated single group attachment of the selected group by an MS, which can operate without a selected group, attachment accepted – 2.1.1	IOP001-01 2.1.1	-
TTR001-01 8.4	Attachment of the selected group MS initiated single group attachment of the selected group, by an MS, which can operate without a selected group, rejection – 2.1.3	IOP001-01 2.1.3	-
TTR001-01 8.4	Attachment of the selected group Null group attachment as the selected group – 2.1.5	IOP001-01 2.1.5	P
TTR001-01 8.4	Attachment of the selected group Change of selected group – 2.1.6	IOP001-01 2.1.6	P
TTR001-01 8.5	Multiple group attachment MS initiated single group attachment of other than selected group, attachment accepted – 2.1.2	IOP001-01 2.1.2	P
TTR001-01 8.5	Multiple group attachment MS initiated single group attachment of other than selected group, rejection – 2.1.4	IOP001-01 2.1.4	N/A
TTR001-01 8.5	Multiple group attachment MS initiated Multiple group attachment during MS registration – 2.2.1	IOP001-01 2.2.1	P
TTR001-01 8.5	Multiple group attachment MS initiated Multiple group attachment with attachment to selected group – 2.2.2	IOP001-01 2.2.2	-
TTR001-01 8.5	Multiple group attachment MS initiated Multiple group attachment with no selected group – 2.2.3	IOP001-01 2.2.3	P
TTR001-01 8.5	Multiple group attachment MS initiated Multiple group attachment, only the attachment of the selected group is accepted – 2.2.4	IOP001-01 2.2.4	N/A
TTR001-01 8.5	Multiple group attachment MS initiated Multiple group attachment, rejection of some of the attached groups – 2.2.5	IOP001-01 2.2.5	N/A
TTR001-01 8.6	MS initiated detachment MS initiated group detachment of the selected group – 2.3.1	IOP001-01 2.3.1	No
TTR001-01 8.6	MS initiated detachment MS initiated group detachment of the selected group and an attached group – 2.3.2	IOP001-01 2.3.2	No
TTR001-01 8.7	SwMI initiated group attachment and detachment		
TTR001-01 8.7.1	SwMI initiated detachment SwMI initiated group detachment with another value than Temporary 1 detachment and attachment – 2.4.1	IOP001-01 2.4.1	N/A
TTR001-01 8.7.1	SwMI initiated detachment SwMI initiated Temporary 1 group detachment and re-attachment of selected group – 2.4.2	IOP001-01 2.4.2	N/A
TTR001-01 8.7.1	SwMI initiated detachment SwMI initiated Temporary 1 group detachment and re-attachment of the non-selected group – 2.4.3	IOP001-01 2.4.3	N/A

Motorola SwMI			Motorola MTH800
TTR001-01 8.7.2	SwMI initiated attachment SwMI initiated group detachment with another value than Temporary 1 detachment and attachment – 2.4.1	IOP001-01 2.4.1	N/A
TTR001-01 8.7.2	SwMI initiated attachment SwMI initiated Temporary 1 group detachment and re-attachment of selected group – 2.4.2	IOP001-01 2.4.2	N/A
TTR001-01 8.7.2	SwMI initiated attachment SwMI initiated Temporary 1 group detachment and re-attachment of the non-selected group – 2.4.3	IOP001-01 2.4.3	N/A
TTR001-01 8.7.4	SwMI initiated location updating with group report request SwMI initiated location updating with group reporting – 1.3.2	IOP001-01 1.3.2	N/A
TTR001-01 8.7.5	SwMI initiated registration without group report request SwMI initiated location updating without group reporting – 1.3.1	IOP001-01 1.3.1	Note 1
TTR001-01 9	Group call		
TTR001-01 9.1	Call set-up Normal Group call – 3.1	IOP001-01 3.1	P
TTR001-01 9.1	Call set-up Group Call set-up, resource queuing – 3.3	IOP001-01 3.3	P
TTR001-01 9.1	Call set-up Group scanning – 3.8	IOP001-01 3.8	P
TTR001-01 9.1	Call set-up MS-ISDN group call – 9.2	IOP001-01 9.2	N/A
TTR001-01 9.1.2	Call set-up modifications Group call-SwMI changes requested call priority – 3.7	IOP001-01 3.7	N/A
TTR001-01 9.2.1	End of transmission Normal Group call – 3.1	IOP001-01 3.1	P
TTR001-01 9.2.1	End of transmission Group scanning – 3.8	IOP001-01 3.8	P
TTR001-01 9.2.2	Request to transmit Normal Group call – 3.1	IOP001-01 3.1	P
TTR001-01 9.2.2	Request to transmit Pre-emptive speech item request, non pre-emptive transmission request queuing – 3.4	IOP001-01 3.4	N/A
TTR001-01 9.2.2	Request to transmit Pre-emptive speech item request, non pre-emptive transmission request rejection – 3.5	IOP001-01 3.5	P
TTR001-01 9.2.2	Request to transmit Group scanning – 3.8	IOP001-01 3.8	P
TTR001-01 9.2.2	Request to transmit MS-ISDN group call – 9.2	IOP001-01 9.2	N/A
TTR001-01 9.3	Call disconnection Normal Group call – 3.1	IOP001-01 3.1	P
TTR001-01 9.3	Call disconnection Group call disconnection by call owner MS – 3.6	IOP001-01 3.6	N/A
TTR001-01 9.4	Late entry Late entry – 3.2	IOP001-01 3.2	P
TTR001-01 9.5	Emergency group call		
TTR001-01 9.5	Emergency group call Emergency call set-up to busy group, speech item interruption – 6.1.1	IOP001-01 6.1.1	P
TTR001-01 9.5	Emergency group call Emergency group call resource pre-emption – 6.1.2	IOP001-01 6.1.2	P
TTR001-01 9.5	Emergency group call Pre-emption during group call restoration. Transmitting (Announced Type 3) – 7.2.5	IOP001-01 7.2.5	P
TTR001-01 9.5.1	Emergency speech item request Emergency call set-up to busy group speech item interruption – 6.1.1	IOP001-01 6.1.1	P
TTR001-01 9.5.2	Emergency group call modification Emergency call set-up, P2MP to P2P call modification – 6.1.3	IOP001-01 6.1.3	N/A
TTR001-01 9.7	Pre-emptive Priority Group Call Group Call, pre-emptive priority, resource pre-emption – 3.9	IOP001-01 3.9	N/A
TTR001-01 9.7	Pre-emptive Priority Group Call Pre-emption of busy user in an individual call, accepted – 3.10	IOP001-01 3.10	N/A
TTR001-01 9.7	Pre-emptive Priority Group Call Pre-emption of busy user in group call, accepted – 3.11	IOP001-01 3.11	N/A
TTR001-01 9.7	Pre-emptive Priority Group Call Pre-emption on busy user, rejected – 3.12	IOP001-01 3.12	N/A
TTR001-01 10	Cell re-selection		
TTR001-01 10.1	Undeclared cell re-selection Cell re-selection without communication activity – 7.1.1	IOP001-01 7.1.1	P
TTR001-01 10.2	Cell re-selection with call restoration		
TTR001-01 10.2.1	Unannounced cell re-selection Group call restoration, Receiving (Unannounced) – 7.2.2	IOP001-01 7.2.2	P
TTR001-01 10.2.1	Unannounced cell re-selection Queuing during Group call restoration, Receiving (Unannounced) – 7.2.4	IOP001-01 7.2.4	P
TTR001-01 10.2.1	Unannounced cell re-selection Individual call restoration, Receiving (Unannounced) – 7.3.2.2	IOP001-01 7.3.2.2	P

Motorola SwMI			Motorola MTH800
TTR001-01 10. 2. 1	Unannounced cell re-selection Individual call restoration, Communication inactivity (Unannounced) – 7.3.3.2	IOP001-01 7. 3. 3. 2	P
TTR001-01 10. 2. 1	Unannounced cell re-selection Queuing during Individual call restoration, Receiving (Unannounced) – 7.3.4.3	IOP001-01 7. 3. 4. 3	P
TTR001-01 10. 2. 1	Unannounced cell re-selection Queuing during individual call restoration, Communication inactivity (Unannounced) – 7.3.5.2	IOP001-01 7. 3. 5. 2	P
TTR001-01 10. 2. 2	Announced cell re-selection Type without Preferred Neighbour Selected Group call restoration, Transmitting. (Announced Type 3) – 7.2.1	IOP001-01 7. 2. 1	P
TTR001-01 10. 2. 2	Announced cell re-selection Type without Preferred Neighbour Selected Queuing during group call restoration, Transmitting (Announced type 3) – 7.2.3	IOP001-01 7. 2. 3	P
TTR001-01 10. 2. 2	Announced cell re-selection Type without Preferred Neighbour Selected Pre-emption during group call restoration. Transmitting. (Announced type 3) – 7.2.5	IOP001-01 7. 2. 5	P
TTR001-01 10. 2. 2	Announced cell re-selection Type without Preferred Neighbour Selected Individual call restoration, Transmitting party (Announced type 3) – 7.3.1.1	IOP001-01 7. 3. 1. 1	P
TTR001-01 10. 2. 2	Announced cell re-selection Type without Preferred Neighbour Selected Individual call restoration, Transmitting party (Radio link failure) – 7.3.1.2	IOP001-01 7. 3. 1. 2	P1
TTR001-01 10. 2. 2	Announced cell re-selection Type without Preferred Neighbour Selected Individual call restoration. Receiving (Announced Type 3) – 7.3.2.1	IOP001-01 7. 3. 2. 1	No
TTR001-01 10. 2. 2	Announced cell re-selection Type without Preferred Neighbour Selected Individual call restoration, Communication inactivity (Announced Type 3) – 7.3.3.1	IOP001-01 7. 3. 3. 1	No
TTR001-01 10. 2. 2	Announced cell re-selection Type without Preferred Neighbour Selected Queuing during individual call restoration, Transmitting – 7.3.4.1	IOP001-01 7. 3. 4. 1	P
TTR001-01 10. 2. 2	Announced cell re-selection Type without Preferred Neighbour Selected Queuing during Individual call restoration, Receiving (Announced Type 3) – 7.3.4.2	IOP001-01 7. 3. 4. 2	No
TTR001-01 10. 2. 2	Announced cell re-selection Type without Preferred Neighbour Selected Queuing during Individual call restoration, Communication inactivity. (Announced Type 3) – 7.3.5.1	IOP001-01 7. 3. 5. 1	No
TTR001-01 10. 2. 2	Announced cell re-selection Type without Preferred Neighbour Selected Duplex call restoration (Announced Type 3) – 7.4.1	IOP001-01 7. 4. 1	P
TTR001-01 10. 2. 2	Announced cell re-selection Type without Preferred Neighbour Selected Queuing during Duplex call restoration (Announced Type 3) – 7.4.2	IOP001-01 7. 4. 2	P
TTR001-01 10. 2. 3	Announced cell re-selection Type with Preferred Neighbour Selected Group call announced cell-reselection with preferred neighbour selected and with call restoration, Transmitting – 7.2.7	IOP001-01 7. 2. 7	N/A
TTR001-01 10. 2. 3	Announced cell re-selection Type with Preferred Neighbour Selected Individual call, Announced cell re-reselection with Preferred Neighbour Selected and with Call Restoration Transmitting – 7.3.6	IOP001-01 7. 3. 6	N/A
TTR001-01 10. 3	Cell re-selection without call restoration		
TTR001-01 10. 3. 1	Announced Type with Preferred Neighbour Selected and without Forward Registration Group call, Announced cell re-selection without Call Restoration, (Seamless Hand-over) without Forward Registration Transmitting – 7.2.6	IOP001-01 7. 2. 6	N/A
TTR001-01 10. 3. 1	Announced Type with Preferred Neighbour Selected and without Forward Registration Duplex call, Announced cell-re-selection without Call Restoration (Seamless Handover), without Forward Registration – 7.4.3	IOP001-01 7. 4. 3	N/A
TTR001-01 10. 3. 2	Announced Type with Preferred Neighbour Selected and with Forward Registration Group call, Announced cell re-selection without Call Restoration with Forward Registration, Transmitting – 7.2.8	IOP001-01 7. 2. 8	N/A
TTR001-01 10. 3. 2	Announced Type with Preferred Neighbour Selected and with Forward Registration Individual call, Announced cell re-selection without Call Restoration with Forward Registration, Transmitting – 7.3.7	IOP001-01 7. 3. 7	N/A

Motorola SwMI			Motorola MTH800
TTR001-01 11	Short data service		
TTR001-01 11. 1. 1	Service Overview MS-ISDN addressed individual Status message – 9.3	IOP001-01 9. 3	N/A
TTR001-01 11. 1. 1	Service Overview MS-ISDN addressed group Status message – 9.4	IOP001-01 9. 4	N/A
TTR001-01 11. 1. 3. 1	MS to Wireline Dispatcher with Status Acknowledge Status transfer to Dispatcher – 5.1.2.2	IOP001-01 5. 1. 2. 2	P
TTR001-01 11. 1. 3. 2	MS to MS/Group with General Status Acknowledge Individual addressed status transfer – 5.1.1	IOP001-01 5. 1. 1	N/A
TTR001-01 11. 1. 3. 2	MS to MS/Group with General Status Acknowledge Status transfer to group – 5.1.2.1	IOP001-01 5. 1. 2. 1	N/A
TTR001-01 11. 1. 3. 2	MS to MS/Group with General Status Acknowledge Status to scanned group – 5.1.2.3	IOP001-01 5. 1. 2. 3	N/A
TTR001-01 11. 1. 3. 2	MS to MS/Group with General Status Acknowledge MS-ISDN addressed individual Status message – 9.3	IOP001-01 9. 3	N/A
TTR001-01 11. 1. 3. 2	MS to MS/Group with General Status Acknowledge MS-ISDN addressed group Status message – 9.4	IOP001-01 9. 4	N/A
TTR001-01 12	Telephone call		
TTR001-01 12. 1	Gateway addresses TETRA-originated call set-up – 8.1	IOP001-01 8. 1	P
TTR001-01 12. 2	Call Set-up		
TTR001-01 12. 2. 1	MS Originated, Late Through-Connect TETRA-originated call set-up – 8.1	IOP001-01 8. 1	-
TTR001-01 12. 2. 2	MS Originated, Early Through-Connect TETRA-originated call set-up – 8.1	IOP001-01 8. 1	P
TTR001-01 12. 2. 3	MS Originated, Call Queued TETRA-originated call set-up queuing – 8.2	IOP001-01 8. 2	P
TTR001-01 12. 2. 4	MS terminated PSTN originated call – 8.3	IOP001-01 8. 3	P
TTR001-01 12. 4	DTMF Over dial TETRA-originated successful DTMF over-dial – 8.4	IOP001-01 8. 4	P
TTR001-01 12. 4	DTMF Over dial TETRA-originated unsuccessful DTMF over-dial – 8.5	IOP001-01 8. 5	N/A
TTR001-01 12. 5	Disconnect Causes TETRA-originated call set-up – 8.1	IOP001-01 8. 1	P
TTR001-01 12. 5	Disconnect Causes TETRA-originated call set-up queuing – 8.2	IOP001-01 8. 2	P
TTR001-01 12. 5	Disconnect Cause PSTN originated call – 8.3	IOP001-01 8. 3	P
TTR001-01 12. 6	Emergency telephone call Emergency call to emergency number – 6.3.1	IOP001-01 6. 3. 1	N/A
TTR001-01 14	Layer 2 operation		
TTR001-01 14. 1. 1. 2	Traffic channel (TCH) Usage of SACCH during group call – 10.2	IOP001-01 10. 2	-
TTR001-01 14. 1. 1. 2	Traffic channel (TCH) Usage of SACCH during individual call – 10.4	IOP001-01 10. 4	-
TTR001-01 14. 1. 1. 2	Traffic channel (TCH) Usage of downlink SACCH, receiving group call – 10.6	IOP001-01 10. 6	P
TTR001-01 14. 1. 1. 2	Traffic channel (TCH) Usage of downlink SACCH, receiving individual call – 10.8	IOP001-01 10. 8	P
TTR001-01 14. 1. 1. 3	Fast Associated Control Channel (FACCH) Usage of downlink FACCH, group call inactivity – 10.5	IOP001-01 10. 5	P
TTR001-01 14. 1. 1. 4	Up-link FACCH and down-link TCH Usage of FACCH during group call – 10.1	IOP001-01 10. 1	N/A
TTR001-01 14. 1. 1. 4	Up-link FACCH and down-link TCH Usage of FACCH during individual call – 10.3	IOP001-01 10. 3	N/A
TTR001-01 14. 1. 1. 5	Downlink FACCH and uplink TCH Usage of downlink FACCH, transmitting individual call – 10.7	IOP001-01 10. 7	N/A
TTR001-02	SDS		
TTR001-02 6	Service Overview		
TTR001-02 6. 1	Addressing MS-ISDN addressed individual SDS-TL message – 9.5 Core	IOP001-01 9. 5	N/A
TTR001-02 6. 1	Addressing MS-ISDN addressed group SDS-TL message – 9.6 Core	IOP001-01 9. 6	N/A
TTR001-02 7	User defined data Type 1, 2 and 3		
TTR001-02 7	User defined data Type 1, 2 and 3 Individual addressed SDS Type 1 transfer – 1.1.1	IOP001-02 1. 1. 1	N/A

Motorola SwMI			Motorola MTH800
TTR001-02 7	User defined data Type 1, 2 and 3 Individual addressed SDS Type 2 transfer – 1.2.1	IOP001-02 1.2.1	N/A
TTR001-02 7	User defined data Type 1, 2 and 3 Individual addressed SDS Type 3 transfer – 1.3.1	IOP001-02 1.3.1	N/A
TTR001-02 8	User defined data Type 4		
TTR001-02 8.1	User defined data Type 4 SDS-TL message to scanned group (without acknowledgement) – 1.4.3	IOP001-02 1.4.3	N/A
TTR001-02 8.1.2	MS to MS, Standard report MS-ISDN addressed individual SDS-TL message – 9.5 Core	IOP001-01 9.5	N/A
TTR001-02 8.1.2	MS to MS, Standard report MS-ISDN addressed group SDS-TL message – 9.6 Core	IOP001-01 9.6	N/A
TTR001-02 8.1.2	MS to MS, Standard report Usage of FACCH during group call – 10.1 Core	IOP001-01 10.1	N/A
TTR001-02 8.1.2	MS to MS, Standard report Usage of SACCH during group call – 10.2 Core	IOP001-01 10.2	-
TTR001-02 8.1.2	MS to MS, Standard report Usage of FACCH during individual call – 10.3 Core	IOP001-01 10.3	N/A
TTR001-02 8.1.2	MS to MS, Standard report Usage of SACCH during individual call – 10.4 Core	IOP001-01 10.4	-
TTR001-02 8.1.2	MS to MS, Standard Report Individual addressed text messaging using SDS-TL, (with acknowledgement) – 1.4.1	IOP001-02 1.4.1	P
TTR001-02 8.1.2	MS to MS, Standard Report Group addressed text messaging using SDS-TL, (without acknowledgement) – 1.4.2	IOP001-02 1.4.2	N/A
TTR001-02 8.1.3	MS to MS, Short report MS-ISDN addressed individual SDS-TL message – 9.5 Core	IOP001-01 9.5	N/A
TTR001-02 8.1.3	MS to MS, Short report Usage of FACCH during individual call – 10.3 Core	IOP001-01 10.3	N/A
TTR001-02 8.1.3	MS to MS, Short report Usage of SACCH during individual call – 10.4 Core	IOP001-01 10.4	N/A
TTR001-02 8.1.3	MS to MS, Short Report Individual addressed text messaging using SDS-TL, (with acknowledgement) – 1.4.1	IOP001-02 1.4.1	N/A
TTR001-02 8.2	Text messaging		
TTR001-02 8.2.1.2	Text Length MS-ISDN addressed individual SDS-TL message – 9.5 Core	IOP001-01 9.5	N/A
TTR001-02 8.2.1.2	Text Length MS-ISDN addressed group SDS-TL message – 9.6 Core	IOP001-01 9.6	N/A
TTR001-02 8.2.1.3	Data Coding Scheme MS-ISDN addressed individual SDS-TL message – 9.5 Core	IOP001-01 9.5	N/A
TTR001-02 8.2.1.3	Data Coding Scheme MS-ISDN addressed group SDS-TL message – 9.6 Core	IOP001-01 9.6	N/A
TTR001-02 8.2.1.4	PDU Contents MS-ISDN addressed individual SDS-TL message – 9.5 Core	IOP001-01 9.5	N/A
TTR001-02 8.2.1.4	PDU Contents MS-ISDN addressed group SDS-TL message – 9.6 Core	IOP001-01 9.6	N/A
TTR001-02 8.2.1.4	PDU Contents Usage of FACCH during group call – 10.1 Core	IOP001-01 10.1	N/A
TTR001-02 8.2.1.4	PDU Contents Usage of SACCH during group call – 10.2 Core	IOP001-01 10.2	-
TTR001-02 8.2.1.4	PDU contents Group addressed text messaging using SDS-TL, (without acknowledgement) – 1.4.2	IOP001-02 1.4.2	N/A
TTR001-02 8.2.1.4	PDU contents SDS-TL message to scanned group (without acknowledgement) – 1.4.3	IOP001-02 1.4.3	N/A
TTR001-03	DGNA		
TTR001-03 7	SS-DGNA not supported		
TTR001-03 7.5	SS-DGNA specific functions not supported SS-DGNA specific function not supported by MS – 1.1.1	IOP001-03 1.1.1	-
TTR001-03 7.5	SS-DGNA specific functions not supported SS-DGNA specific function not supported by SwMI – 1.1.2	IOP001-03 1.1.2	-
TTR001-03 8	Supported SS-DGNA functions		
TTR001-03 8.1	Group assignment		
TTR001-03 8.1	Group assignment DGNA assignment without attachment – 1.2.1	IOP001-03 1.2.1	P

Motorola SwMI			Motorola MTH800
TTR001-03 8.1	Group assignment DGNA assign with attachment as selected group, MS has no selected group – 1.3.1	IOP001-03 1.3.1	N/A
TTR001-03 8.1	Group assignment DGNA assign with attachment as selected group, MS has selected group – 1.3.2	IOP001-03 1.3.2	N/A
TTR001-03 8.1	Group assignment DGNA assign with attachment, attachment not allowed at next ITSI attach – 1.4.1	IOP001-03 1.4.1	N/A
TTR001-03 8.1	Group assignment DGNA assign with attachment, attachment required at next ITSI attach – 1.4.2	IOP001-03 1.4.2	N/A
TTR001-03 8.1	Group assignment DGNA assign with attachment, pre programmed group – 1.4.3	IOP001-03 1.4.3	N/A
TTR001-03 8.1	Group assignment DGNA assign with attachment as scanned group, MS has selected group – 1.5.1	IOP001-03 1.5.1	N/A
TTR001-03 8.1	Group assignment DGNA assign, with embedded attachment rejected by MS – 1.6.1	IOP001-03 1.6.1	N/A
TTR001-03 8.1.1	Assignment of a group without attachment DGNA assignment without attachment – 1.2.1	IOP001-03 1.2.1	P
TTR001-03 8.1.2	Assignment of a group with attachment DGNA assign with attachment as selected group, MS has no selected group – 1.3.1	IOP001-03 1.3.1	N/A
TTR001-03 8.1.2	Assignment of a group with attachment DGNA assign with attachment as selected group, MS has selected group – 1.3.2	IOP001-03 1.3.2	N/A
TTR001-03 8.1.2	Assignment of a group with attachment DGNA assign with attachment, attachment not allowed at next ITSI attach – 1.4.1	IOP001-03 1.4.1	N/A
TTR001-03 8.1.2	Assignment of a group with attachment DGNA assign with attachment, attachment required at next ITSI attach – 1.4.2	IOP001-03 1.4.2	N/A
TTR001-03 8.1.2	Assignment of a group with attachment DGNA assign with attachment as scanned group, MS has selected group – 1.5.1	IOP001-03 1.5.1	N/A
TTR001-03 8.1.2	Assignment of a group with attachment DGNA assign, with embedded attachment rejected by MS – 1.6.1	IOP001-03 1.6.1	N/A
TTR001-03 8.2	Group de-assignment		
TTR001-03 8.2	Group de-assignment Removing radio subscriber from selected DGNA group – 1.7.1	IOP001-03 1.7.1	P
TTR001-03 8.2	Group de-assignment De-assignment of MS from pre-programmed selected group – 1.7.2	IOP001-03 1.7.2	P
TTR001-03 8.2	Group de-assignment De-assignment of MS from pre-programmed scanned group – 1.7.3	IOP001-03 1.7.3	-
TTR001-04	AUTHENTICATION		
TTR001-04 7	Authentication functions		
TTR001-04 7.1	SwMI initiated authentication Successful ITSI attach with authentication – 1.1.1	IOP001-04 1.1.1	P
TTR001-04 7.1	SwMI initiated authentication Rejected registration, authentication failure – 1.1.2	IOP001-04 1.1.2	P
TTR001-04 7.1	SwMI initiated authentication Successful roaming location update with authentication – 1.1.3	IOP001-04 1.1.3	N/A
TTR001-05	PACKET DATA		
TTR001-05 7	Packet Data functions		
TTR001-05 7.1	Context Activation		
TTR001-05 7.1.1	TE IPCP Initiated, Static Address (TE supplied) Packet Data context activation, static IP address – 1.1.1	IOP001-05 1.1.1	P
TTR001-05 7.1.2	TE IPCP Initiated, Dynamic Address Packet Data context activation, dynamic IP address – 1.1.2	IOP001-05 1.1.2	P
TTR001-05 7.1.3	User Authentication using PAP Packet Data context activation, with PAP user authentication – 1.1.3	IOP001-05 1.1.3	P
TTR001-05 7.1.3	User Authentication using PAP Packet Data context activation, APN index selected – 1.1.5	IOP001-05 1.1.5	N/A
TTR001-05 7.1.4	User Authentication using CHAP Packet Data context activation, with CHAP user authentication – 1.1.4	IOP001-05 1.1.4	P
TTR001-05 7.1.5	Failed user authentication Packet Data context activation rejected, PAP user authentication – 1.1.7	IOP001-05 1.1.7	P
TTR001-05 7.1.5	Failed user authentication Packet Data context activation rejected, CHAP user authentication – 1.1.8	IOP001-05 1.1.8	P
TTR001-05 7.1.6	Provisioning Reject Packet Data context activation, activation rejected – 1.1.6	IOP001-05 1.1.6	P
TTR001-05 7.1.6	Provisioning Reject Packet Data context activation rejected, invalid APN index selected – 1.1.9	IOP001-05 1.1.9	N/A

Motorola SwMI			Motorola MTH800
TTR001-05 7. 2	Context Deactivation		
TTR001-05 7. 2. 1	MS initiated deactivation Packet Data context deactivation, MS initiated, AL not established – 1.2.3	IOP001-05 1. 2. 3	P
TTR001-05 7. 2. 1	MS initiated deactivation Packet Data context deactivation, MS initiated, AL established – 1.2.4	IOP001-05 1. 2. 4	P
TTR001-05 7. 2. 1. 1	Explicit on SwMI PDCH access Data transmission, SwMI initiated PDCH access, MS reject – 1.3.7	IOP001-05 1. 3. 7	P
TTR001-05 7. 2. 2	SwMI initiated deactivation Packet Data context deactivation, SwMI initiated, AL not established – 1.2.1	IOP001-05 1. 2. 1	P
TTR001-05 7. 2. 2	SwMI initiated deactivation Packet Data context deactivation, SwMI initiated, AL established – 1.2.2	IOP001-05 1. 2. 2	P
TTR001-05 7. 3	PDCH Access		
TTR001-05 7. 3. 1	MS Initiated access on the MCCH Data transmission, MS initiated PDCH access, AL not established, no AL QoS re-negotiation – 1.3.1	IOP001-05 1. 3. 1	P
TTR001-05 7. 3. 1	MS Initiated access on the MCCH Data transmission, MS initiated PDCH access, AL not established, AL QoS re-negotiation – 1.3.2	IOP001-05 1. 3. 2	P
TTR001-05 7. 3. 1	MS Initiated access on the MCCH Data transmission, MS initiated PDCH access, AL established – 1.3.3	IOP001-05 1. 3. 3	P
TTR001-05 7. 3. 2	SwMI initiated access on the MCCH Data transmission, SwMI initiated PDCH access, AL not established – 1.3.4	IOP001-05 1. 3. 4	P
TTR001-05 7. 3. 2	SwMI initiated access on the MCCH Data transmission, SwMI initiated PDCH access, AL established – 1.3.5	IOP001-05 1. 3. 5	P
TTR001-05 7. 3. 3	MS Initiated Access Reject Data transmission, MS initiated PDCH access, SwMI reject – 1.3.6	IOP001-05 1. 3. 6	P
TTR001-05 7. 4	SN Data transfer		
TTR001-05 7. 4	SN-DATA transfer Data transmission, MS initiated PDCH access, AL not established, no AL QoS re-negotiation – 1.3.1	IOP001-05 1. 3. 1	P
TTR001-05 7. 4	SN-DATA transfer PDCH Access, Data transmission, MS initiated PDCH access, AL not established, AL QoS re-negotiation – 1.3.2	IOP001-05 1. 3. 2	P
TTR001-05 7. 4	SN-DATA transfer Data transmission, MS initiated PDCH access, AL established – 1.3.3	IOP001-05 1. 3. 3	P
TTR001-05 7. 4	SN-DATA transfer Data transmission, SwMI initiated PDCH access, AL not established – 1.3.4	IOP001-05 1. 3. 4	P
TTR001-05 7. 4	SN-DATA transfer Data transmission, SwMI initiated PDCH access, AL established – 1.3.5	IOP001-05 1. 3. 5	P
TTR001-05 7. 5	End of Data		
TTR001-05 7. 5. 1	Normal Data transmission, MS initiated PDCH access, AL not established, no AL QoS re-negotiation – 1.3.1	IOP001-05 1. 3. 1	P
TTR001-05 7. 5. 1	Normal Data transmission, MS initiated PDCH access, AL not established, AL QoS re-negotiation - 1.3.2	IOP001-05 1. 3. 2	P
TTR001-05 7. 5. 1	Normal Data transmission, MS initiated PDCH access, AL established – 1.3.3	IOP001-05 1. 3. 3	P
TTR001-05 7. 5. 1	Normal Data transmission, SwMI initiated PDCH access, AL not established – 1.3.4	IOP001-05 1. 3. 4	P
TTR001-05 7. 5. 1	Normal Data transmission, SwMI initiated PDCH access, AL established – 1.3.5	IOP001-05 1. 3. 5	P
TTR001-05 7. 5. 1	Normal Cell re-selection during data transmission – 1.4.1	IOP001-05 1. 4. 1	P
TTR001-05 7. 5. 1	Normal Cell re-selection without data transmission at MS side, READY state – 1.4.2	IOP001-05 1. 4. 2	P
TTR001-05 7. 5. 1	Normal Cell re-selection without data transmission, STANDBY state – 1.4.3	IOP001-05 1. 4. 3	P
TTR001-05 7. 6	Advanced Link Set-up		
TTR001-05 7. 6. 1	MS initiated AL Set-up Data transmission, MS initiated PDCH access, AL not established, no AL QoS re-negotiation – 1.3.1	IOP001-05 1. 3. 1	P
TTR001-05 7. 6. 1	MS Initiated AL Set-up Data transmission, MS initiated PDCH access, AL not established, AL QoS re-negotiation – 1.3.2	IOP001-05 1. 3. 2	P
TTR001-05 7. 6. 1	MS initiated AL Set-up Data transmission, SwMI initiated PDCH access, AL not established – 1.3.4	IOP001-05 1. 3. 4	P
TTR001-05 7. 6. 2	MS Initiated AL Reset Cell re-selection during data transmission – 1.4.1	IOP001-05 1. 4. 1	-
TTR001-05 7. 7	Advanced Link Data Transfer		
TTR001-05 7. 7. 1	Normal Down-link Data transmission, SwMI initiated PDCH access, AL not established – 1.3.4	IOP001-05 1. 3. 4	P
TTR001-05 7. 7. 1	Normal Down-link Data transmission, SwMI initiated PDCH access, AL established – 1.3.5	IOP001-05 1. 3. 5	P

Motorola SwMI			Motorola MTH800
TTR001-05 7.7.4	Normal Up-link Data transmission, MS initiated PDCH access, AL not established, no AL QoS re-negotiation – 1.3.1	IOP001-05 1.3.1	P
TTR001-05 7.7.4	Normal Up-link Data transmission, MS initiated PDCH access, AL not established, AL QoS re-negotiation – 1.3.2	IOP001-05 1.3.2	P
TTR001-05 7.7.4	Normal Up-link Data transmission, MS initiated PDCH access, AL established – 1.3.3	IOP001-05 1.3.3	P
TTR001-05 7.7.4	Normal Up-link Cell re-selection without data transmission, STANDBY state – 1.4.3	IOP001-05 1.4.3	P
TTR001-05 7.8	Advanced Link Disconnection		
TTR001-05 7.8.1	MS initiated Context Deactivation Packet Data context deactivation, MS initiated, AL established – 1.2.4	IOP001-05 1.2.4	P
TTR001-05 7.8.2	SwMI initiated Context Deactivation Packet Data context deactivation, SwMI initiated, AL established – 1.2.2	IOP001-05 1.2.2	F1
TTR001-05 7.10	Cell re-selection		
TTR001-05 7.10.1	BS Data Cell re-selection without data transmission at MS side, READY state – 1.4.2	IOP001-05 1.4.2	P
TTR001-05 7.10.2	MS Data Cell re-selection during data transmission – 1.4.1	IOP001-05 1.4.1	P
TTR001-09	AMBIENCE LISTENING		
TTR001-09 2.5	SS-AL Signalling		
TTR001-09 2.5.1	SS-AL Call set-up Ambience listening call set-up – 1.1	IOP001-09 1.1	P
TTR001-09 2.5.2	SwMI initiated disconnection of SS-AL call Ambience listening call set-up – 1.1	IOP001-09 1.1	P
TTR001-09 2.5.2	SwMI initiated disconnection of SS-AL call Ambience Listening Call set-up to MS that has an active PDP context – 1.5	IOP001-09 1.5	P
TTR001-09 2.5.4	Affected user MS receives a new call request from the SwMI during SS-AL call MS makes a new individual call during Ambience Listening call – 1.2	IOP001-09 1.2	P
TTR001-09 2.5.5.1	PDP context activation during SS-AL call MS activates PDP context during Ambience Listening call – 1.3	IOP001-09 1.3	P
TTR001-09 2.5.5.2	MS attempts to start a packet data instance during SS-AL call MS starts Packet Data transfer during Ambience Listening call – 1.4	IOP001-09 1.4	P
TTR001-09 2.5.5.4	SS-AL call set-up to MS that has an active PDP context Ambience Listening Call set-up to MS that has an active PDP context – 1.5	IOP001-09 1.5	P
TTR001-11	AIE		
TTR001-11 2.3.5	DCK Retrieval supported by SwMI		
TTR001-11 2.3.5	DCK retrieval supported by SwMI Undeclared cell re-selection (without DCK forwarding request) with clear location updating, including request for CCK – 2.2.1.1	IOP001-11 2.2.1.1	P
TTR001-11 2.3.5	DCK retrieval supported by SwMI Undeclared cell re-selection (without DCK forwarding request) with clear location updating, without request for CCK – 2.2.1.2	IOP001-11 2.2.1.2	N/A
TTR001-11 2.3.5	DCK retrieval supported by SwMI Undeclared cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.1.3	IOP001-11 2.2.1.3	N/A
TTR001-11 2.3.5	DCK retrieval supported by SwMI Undeclared cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.1.4	IOP001-11 2.2.1.4	N/A
TTR001-11 2.3.5	DCK retrieval supported by SwMI Undeclared cell re-selection, encrypted location update using DCK retrieval, including request for CCK – 2.2.1.5	IOP001-11 2.2.1.5	No
TTR001-11 2.3.5	DCK retrieval supported by SwMI Undeclared cell re-selection, encrypted location update using DCK retrieval, without request for CCK – 2.2.1.6	IOP001-11 2.2.1.6	P
TTR001-11 2.3.5	DCK retrieval supported by SwMI Unannounced cell re-selection (without DCK forwarding) with clear location updating, including request for CCK – 2.2.2.1	IOP001-11 2.2.2.1	P
TTR001-11 2.3.5	DCK retrieval supported by SwMI Unannounced cell re-selection (without DCK forwarding) with clear location updating, without request for CCK – 2.2.2.2	IOP001-11 2.2.2.2	N/A
TTR001-11 2.3.5	DCK retrieval supported by SwMI Unannounced cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.2.3	IOP001-11 2.2.2.3	N/A

Motorola SwMI			Motorola MTH800
TTR001-11 2.3.5	DCK retrieval supported by SwMI Unannounced cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.2.4	IOP001-11 2.2.2.4	N/A
TTR001-11 2.3.5	DCK retrieval supported by SwMI Unannounced cell re-selection, encrypted location update using DCK retrieval, including request for CCK – 2.2.2.5	IOP001-11 2.2.2.5	No
TTR001-11 2.3.5	DCK retrieval supported by SwMI Unannounced cell re-selection, encrypted location update using DCK retrieval, without request for CCK – 2.2.2.6	IOP001-11 2.2.2.6	P
TTR001-11 2.3.5	DCK retrieval supported by SwMI Announced type 3 cell re-selection (without DCK forwarding request) with clear location updating, including request for CCK – 2.2.3.1	IOP001-11 2.2.3.1	P
TTR001-11 2.3.5	DCK retrieval supported by SwMI Announced type 3 cell re-selection (without DCK forwarding request) with clear location updating, without request for CCK – 2.2.3.2	IOP001-11 2.2.3.2	N/A
TTR001-11 2.3.5	DCK retrieval supported by SwMI Announced type 3 cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.3.3	IOP001-11 2.2.3.3	N/A
TTR001-11 2.3.5	DCK retrieval supported by SwMI Announced type 3 cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.3.4	IOP001-11 2.2.3.4	N/A
TTR001-11 2.3.5	DCK retrieval supported by SwMI Announced type 3 cell re-selection, encrypted location update using DCK retrieval, including request for CCK – 2.2.3.5	IOP001-11 2.2.3.5	No
TTR001-11 2.3.5	DCK retrieval supported by SwMI Announced type 3 cell re-selection, encrypted location update using DCK retrieval, without request for CCK – 2.2.3.6	IOP001-11 2.2.3.6	P
TTR001-11 2.3.6	Security Class 2, Location update		
TTR001-11 2.3.6	Security Class 2 Registration with encryption applied. Authentication not required by SwMI – 1.1.1	IOP001-11 1.1.1	P
TTR001-11 2.3.6	Security Class 2 Registration with encryption applied. Authentication required by SwMI – 1.1.2	IOP001-11 1.1.2	P
TTR001-11 2.3.6	Security Class 2 Registration without encryption applied. Authentication not required by SwMI – 1.1.3	IOP001-11 1.1.3	-
TTR001-11 2.3.6	Security Class 2 Registration without encryption applied. Authentication required by SwMI – 1.1.4	IOP001-11 1.1.4	-
TTR001-11 2.3.6	Security Class 2 Undeclared cell re-selection – 1.2.1	IOP001-11 1.2.1	P
TTR001-11 2.3.6	Security Class 2 Unannounced cell re-selection – 1.2.2	IOP001-11 1.2.2	P
TTR001-11 2.3.7	Security Class 3, Location update		
TTR001-11 2.3.7	Security Class 3 Class 3 MS Registration with Class 3 ciphering and CCK request, without encryption applied – 2.1.1	IOP001-11 2.1.1	P
TTR001-11 2.3.7	Security Class 3 Class 3 MS Registration with Class 3 ciphering and optional CCK request, with encryption applied – 2.1.2	IOP001-11 2.1.2	P
TTR001-11 2.3.7	Security Class 3 Undeclared cell re-selection (without DCK forwarding request) with clear location updating, including request for CCK – 2.2.1.1	IOP001-11 2.2.1.1	P
TTR001-11 2.3.7	Security Class 3 Undeclared cell re-selection (without DCK forwarding request) with clear location updating, without request for CCK – 2.2.1.2	IOP001-11 2.2.1.2	N/A
TTR001-11 2.3.7	Security Class 3 Undeclared cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.1.3	IOP001-11 2.2.1.3	N/A
TTR001-11 2.3.7	Security Class 3 Undeclared cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.1.4	IOP001-11 2.2.1.4	N/A
TTR001-11 2.3.7	Security Class 3 Undeclared cell re-selection, encrypted location update, using DCK retrieval, including request for CCK – 2.2.1.5	IOP001-11 2.2.1.5	No
TTR001-11 2.3.7	Security Class 3 Undeclared cell re-selection, encrypted location update using DCK retrieval, without request for CCK – 2.2.1.6	IOP001-11 2.2.1.6	P
TTR001-11 2.3.7	Security Class 3 Unannounced cell re-selection (without DCK forwarding) with clear location updating, including request for CCK – 2.2.2.1	IOP001-11 2.2.2.1	P
TTR001-11 2.3.7	Security Class 3 Unannounced cell re-selection (without DCK forwarding) with clear location updating, without request for CCK – 2.2.2.2	IOP001-11 2.2.2.2	N/A

Motorola SwMI			Motorola MTH800
TTR001-11 2.3.7	Security Class 3 Unannounced cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.2.3	IOP001-11 2.2.2.3	N/A
TTR001-11 2.3.7	Security Class 3 Unannounced cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.2.4	IOP001-11 2.2.2.4	N/A
TTR001-11 2.3.7	Security Class 3 Unannounced cell re-selection, encrypted location update using DCK retrieval, including request for CCK – 2.2.2.5	IOP001-11 2.2.2.5	No
TTR001-11 2.3.7	Security Class 3 Unannounced cell re-selection, encrypted location update using DCK retrieval, without request for CCK – 2.2.2.6	IOP001-11 2.2.2.6	P
TTR001-11 2.3.7	Security Class 3 Announced type 3 cell re-selection (without DCK forwarding request) with clear location updating, including request for CCK – 2.2.3.1	IOP001-11 2.2.3.1	P
TTR001-11 2.3.7	Security Class 3 Announced type 3 cell re-selection (without DCK forwarding request) with clear location updating, without request for CCK – 2.2.3.2	IOP001-11 2.2.3.2	N/A
TTR001-11 2.3.7	Security Class 3 Announced type 3 cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.3.3	IOP001-11 2.2.3.3	N/A
TTR001-11 2.3.7	Security Class 3 Announced type 3 cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.3.4	IOP001-11 2.2.3.4	N/A
TTR001-11 2.3.7	Security Class 3 Announced type 3 cell re-selection, encrypted location update using DCK retrieval, including request for CCK – 2.2.3.5	IOP001-11 2.2.3.5	No
TTR001-11 2.3.7	Security Class 3 Announced type 3 cell re-selection, encrypted location update using DCK retrieval, without request for CCK – 2.2.3.6	IOP001-11 2.2.3.6	P
TTR001-11 2.3.7	Security Class 3 Announced cell re-selection with Preferred Neighbour Selected and with Call Restoration, Transmitting encrypted group call, with OTAR of CCK – 2.2.4.1	IOP001-11 2.2.4.1	N/A
TTR001-11 2.3.7	Security Class 3 Announced cell re-selection with Preferred Neighbour Selected and with Call Restoration, Transmitting encrypted group call, without OTAR of CCK – 2.2.4.2	IOP001-11 2.2.4.2	N/A
TTR001-11 2.3.7	Security Class 3 SwMI initiated change of CCK on the serving Cell before group call - Future CCK known to MS – 2.5.3	IOP001-11 2.5.3	P
TTR001-11 2.3.8	DCK Forwarding using announced type 1 cell re-selection		
TTR001-11 2.3.8	DCK Forwarding using announced type 1 cell re-selection SwMI initiated change of CCK on the serving Cell before group call - Future CCK known to MS – 2.5.3	IOP001-11 2.5.3	N/A
TTR001-11 2.3.9	DCK Forwarding using announced type 2 cell re-selection		
TTR001-11 2.3.9	DCK Forwarding using announced type 2 cell re-selection Announced cell re-selection with Preferred Neighbour Selected and with Call Restoration, Transmitting encrypted group call, with OTAR of CCK – 2.2.4.1	IOP001-11 2.2.4.1	N/A
TTR001-11 2.3.9	DCK Forwarding using announced type 2 cell re-selection Announced cell re-selection with Preferred Neighbour Selected and with Call Restoration, Transmitting encrypted group call, without OTAR of CCK – 2.2.4.2	IOP001-11 2.2.4.2	N/A
TTR001-11 2.3.9	DCK Forwarding using announced type 2 cell re-selection SwMI initiated change of CCK on the serving Cell before group call - Future CCK known to MS – 2.5.3	IOP001-11 2.5.3	N/A
TTR001-11 2.3.10	DCK forwarding using OTAR PREPARE and OTAR NEW CELL		
TTR001-11 2.3.10	DCK forwarding using OTAR PREPARE and OTAR NEW CELL Undeclared cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.1.3	IOP001-11 2.2.1.3	N/A
TTR001-11 2.3.10	DCK forwarding using OTAR PREPARE and OTAR NEW CELL Undeclared cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.1.4	IOP001-11 2.2.1.4	N/A
TTR001-11 2.3.10	DCK forwarding using OTAR PREPARE and OTAR NEW CELL Unannounced cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.2.3	IOP001-11 2.2.2.3	N/A
TTR001-11 2.3.10	DCK forwarding using OTAR PREPARE and OTAR NEW CELL Unannounced cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.2.4	IOP001-11 2.2.2.4	N/A

Motorola SwMI			Motorola MTH800
TTR001-11 2. 3.10	DCK Forwarding using OTAR PREPARE and OTAR NEWCELL Announced type 3 cell re-selection (without DCK forwarding request) with clear location updating, including request for CCK – 2.2.3.1	IOP001-11 2. 2. 3. 1	-
TTR001-11 2. 3.10	DCK forwarding using OTAR PREPARE and OTAR NEW CELL Announced type 3 cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.3.3	IOP001-11 2. 2. 3. 3	N/A
TTR001-11 2. 3.10	DCK forwarding using OTAR PREPARE and OTAR NEW CELL Announced type 3 cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.3.4	IOP001-11 2. 2. 3. 4	N/A
TTR001-11 2. 3.10	DCK forwarding using OTAR PREPARE and OTAR NEW CELL SwMI initiated change of CCK on the serving Cell before group call - Future CCK known to MS – 2.5.3	IOP001-11 2. 5. 3	-
TTR001-11 2. 3.11	Change of Security Class or Cipher Key on the serving cell		
TTR001-11 2. 3.11	Change of Security Class or Cipher Key on the serving cell SwMI initiated change of CCK on the serving cell before group call - Future CCK unknown to MS – 2.5.1	IOP001-11 2. 5. 1	P
TTR001-11 2. 3.11	Change of Security Class or Cipher Key on the serving Cell SwMI initiated change of CCK on the serving Cell during group call - Future CCK unknown to MS – 2.5.2	IOP001-11 2. 5. 2	P
TTR001-11 2. 3.11	Change of Security Class or Cipher Key on the serving cell SwMI initiated change of CCK on the serving Cell before group call - Future CCK known to MS – 2.5.3	IOP001-11 2. 5. 3	P
TTR001-11 2. 3.11. 4	D-CK CHANGE DEMAND (Change of Cipher Key – Absolute IV) SwMI initiated change of CCK on the serving cell before group call - Future CCK unknown to MS – 2.5.1	IOP001-11 2. 5. 1	P
TTR001-11 2. 3.11. 4	D-CK CHANGE DEMAND (Change of Cipher Key – Absolute IV) SwMI initiated change of CCK on the serving Cell during group call - Future CCK unknown to MS – 2.5.2	IOP001-11 2. 5. 2	P
TTR001-11 2. 3.11. 4	D-CK CHANGE DEMAND (Change of Cipher Key – Absolute IV) SwMI initiated change of CCK on the serving Cell before group call - Future CCK known to MS – 2.5.3	IOP001-11 2. 5. 3	P
TTR001-11 2. 3.11. 5	D-CK CHANGE DEMAND (Change of Cipher Key – Immediate) SwMI initiated change of CCK on the serving cell before group call - Future CCK unknown to MS – 2.5.1	IOP001-11 2. 5. 1	N/A
TTR001-11 2. 3.11. 5	D-CK CHANGE DEMAND (Change of Cipher Key – Immediate) SwMI initiated change of CCK on the serving Cell during group call - Future CCK unknown to MS – 2.5.2	IOP001-11 2. 5. 2	N/A
TTR001-11 2. 3.11. 5	D-CK CHANGE DEMAND (Change of Cipher Key – Immediate) SwMI initiated change of CCK on the serving Cell before group call - Future CCK known to MS – 2.5.3	IOP001-11 2. 5. 3	N/A
TTR001-11 2. 3.15. 1	MS CCK Management SwMI initiated change of CCK on the serving Cell during group call - Future CCK unknown to MS – 2.5.2	IOP001-11 2. 5. 2	P
TTR001-11 2. 3.16	Call Related Signalling		
TTR001-11 2. 3.16	Call Related Signalling Call from Class 2 MS to Class 2 MS 1.3.1.1	IOP001-11 1. 3. 1. 1	P
TTR001-11 2. 3.16	Call Related Signalling Call from Class 2 MS to Class 1 MS – 1.3.1.2	IOP001-11 1. 3. 1. 2	P
TTR001-11 2. 3.16	Call Related Signalling Call from Class 1 MS to Class 2 MS – 1.3.1.3	IOP001-11 1. 3. 1. 3	P
TTR001-11 2. 3.16	Call Related Signalling Call from Class 2 MS to Class 2 Group – 1.3.2.1	IOP001-11 1. 3. 2. 1	P
TTR001-11 2. 3.16	Call Related Signalling Call from Class 2 MS to Class 1 Group – 1.3.2.2	IOP001-11 1. 3. 2. 2	P
TTR001-11 2. 3.16	Call Related Signalling Unannounced cell re-selection (without DCK forwarding) with clear location updating, including request for CCK – 2.2.2.1	IOP001-11 2. 2. 2. 1	P
TTR001-11 2. 3.16	Call Related Signalling Unannounced cell re-selection (without DCK forwarding) with clear location updating, without request for CCK – 2.2.2.2	IOP001-11 2. 2. 2. 2	N/A
TTR001-11 2. 3.16	Call Related Signalling Unannounced cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.2.3	IOP001-11 2. 2. 2. 3	N/A
TTR001-11 2. 3.16	Call Related Signalling Unannounced cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.2.4	IOP001-11 2. 2. 2. 4	N/A

Motorola SwMI			Motorola MTH800
TTR001-11 2. 3.16	Call Related Signalling Unannounced cell re-selection, encrypted location update using DCK retrieval, including request for CCK – 2.2.2.5	IOP001-11 2. 2. 2. 5	No
TTR001-11 2. 3.16	Call Related Signalling Unannounced cell re-selection, encrypted location update using DCK retrieval, without request for CCK – 2.2.2.6	IOP001-11 2. 2. 2. 6	P
TTR001-11 2. 3.16	Call Related Signalling Encrypted individual call from Class 3 MS to Class 3 MS – 2.3.1.1	IOP001-11 2. 3. 1. 1	P
TTR001-11 2. 3.16	Call Related Signalling Individual call from Class 3 MS to Class 1 MS – 2.3.1.2	IOP001-11 2. 3. 1. 2	P
TTR001-11 2. 3.16	Call Related Signalling Individual call from Class 1 MS to Class 3 MS – 2.3.1.3	IOP001-11 2. 3. 1. 3	P
TTR001-11 2. 3.16	Call Related Signalling Encrypted group call from Class 3 MS to Class 3 Group – 2.3.2.1	IOP001-11 2. 3. 2. 1	P
TTR001-11 2. 3.16	Call Related Signalling Group call from Class 3 MS to Class 1 Group – 2.3.2.2	IOP001-11 2. 3. 2. 2	P
TTR001-11 2. 3.17	Call Unrelated Signalling		
TTR001-11 2. 3.17	Call Unrelated Signalling Status from Class 2 MS in Class 1 Group call to idle Class 2 MS – 1.4.1	IOP001-11 1. 4. 1	N/A
TTR001-11 2. 3.17	Call Unrelated Signalling Status from idle Class 2 MS to Class 2 MS in Class 1 group call – 1.4.2	IOP001-11 1. 4. 2	N/A
TTR001-11 2. 3.17	Call Unrelated Signalling Status from Class 3 MS in Class 1 Group call to Class 3 MS – 2.4.1	IOP001-11 2. 4. 1	N/A
TTR001-11 2. 3.17	Call Unrelated Signalling Status from Class 3 MS to Class 3 MS in Class 1 Group call – 2.4.2	IOP001-11 2. 4. 2	N/A
TTR001-11 2. 3.20	AI Signalling Protection		
TTR001-11 2. 3.20	AI Signalling Protection Registration with encryption applied. Authentication not required by SwMI – 1.1.1	IOP001-11 1. 1. 1	P
TTR001-11 2. 3.20	AI Signalling Protection Registration with encryption applied. Authentication required by SwMI – 1.1.2	IOP001-11 1. 1. 2	P
TTR001-11 2. 3.20	AI Signalling Protection Registration without encryption applied. Authentication not required by SwMI – 1.1.3	IOP001-11 1. 1. 3	-
TTR001-11 2. 3.20	AI Signalling Protection Registration without encryption applied. Authentication required by SwMI – 1.1.4	IOP001-11 1. 1. 4	-
TTR001-11 2. 3.20	AI Signalling Protection Undeclared cell re-selection – 1.2.1	IOP001-11 1. 2. 1	P
TTR001-11 2. 3.20	AI Signalling Protection Unannounced cell re-selection – 1.2.2	IOP001-11 1. 2. 2	P
TTR001-11 2. 3.20	AI Signalling Protection Class 3 MS Registration with Class 3 ciphering and CCK request, without encryption applied – 2.1.1	IOP001-11 2. 1. 1	P
TTR001-11 2. 3.20	AI Signalling Protection Class 3 MS Registration with Class 3 ciphering and optional CCK request, with encryption applied – 2.1.2	IOP001-11 2. 1. 2	P
TTR001-11 2. 3.20	AI Signalling Protection Undeclared cell re-selection (without DCK forwarding request) with clear location updating, including request for CCK – 2.2.1.1	IOP001-11 2. 2. 1. 1	P
TTR001-11 2. 3.20	AI Signalling Protection Undeclared cell re-selection (without DCK forwarding request) with clear location updating, without request for CCK – 2.2.1.2	IOP001-11 2. 2. 1. 2	N/A
TTR001-11 2. 3.20	AI Signalling Protection Undeclared cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.1.3	IOP001-11 2. 2. 1. 3	N/A
TTR001-11 2. 3.20	AI Signalling Protection Undeclared cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.1.4	IOP001-11 2. 2. 1. 4	N/A
TTR001-11 2. 3.20	AI Signalling Protection Undeclared cell re-selection, encrypted location update using retrieval, including request for CCK – 2.2.1.5	IOP001-11 2. 2. 1. 5	No
TTR001-11 2. 3.20	AI Signalling Protection Undeclared cell re-selection, encrypted location update using DCK retrieval, without request for CCK – 2.2.1.6	IOP001-11 2. 2. 1. 6	P
TTR001-11 2. 3.20	AI Signalling Protection Unannounced cell re-selection (without DCK forwarding) with clear location updating, including request for CCK – 2.2.2.1	IOP001-11 2. 2. 2. 1	P
TTR001-11 2. 3.20	AI Signalling Protection Unannounced cell re-selection (without DCK forwarding) with clear location updating, without request for CCK – 2.2.2.2	IOP001-11 2. 2. 2. 2	N/A

Motorola SwMI			Motorola MTH800
TTR001-11 2. 3.20	AI Signalling Protection Unannounced cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.2.3	IOP001-11 2. 2. 2. 3	N/A
TTR001-11 2. 3.20	AI Signalling Protection Unannounced cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.2.4	IOP001-11 2. 2. 2. 4	N/A
TTR001-11 2. 3.20	AI Signalling Protection Unannounced cell re-selection, encrypted location update using DCK retrieval, including request for CCK – 2.2.2.5	IOP001-11 2. 2. 2. 5	No
TTR001-11 2. 3.20	AI Signalling Protection Unannounced cell re-selection, encrypted location update using DCK retrieval, without request for CCK – 2.2.2.6	IOP001-11 2. 2. 2. 6	P
TTR001-11 2. 3.20	AI Signalling Protection Announced type 3 cell re-selection (without DCK forwarding request) with clear location updating, including request for CCK – 2.2.3.1	IOP001-11 2. 2. 3. 1	P
TTR001-11 2. 3.20	AI Signalling Protection Announced type 3 cell re-selection (without DCK forwarding request) with clear location updating, without request for CCK – 2.2.3.2	IOP001-11 2. 2. 3. 2	N/A
TTR001-11 2. 3.20	AI Signalling Protection Announced type 3 cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.3.3	IOP001-11 2. 2. 3. 3	N/A
TTR001-11 2. 3.20	AI Signalling Protection Announced type 3 cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.3.4	IOP001-11 2. 2. 3. 4	N//A
TTR001-11 2. 3.20	AI Signalling Protection Announced type 3 cell re-selection, encrypted location update using DCK retrieval, including request for CCK – 2.2.3.5	IOP001-11 2. 2. 3. 5	No
TTR001-11 2. 3.20	AI Signalling Protection Announced type 3 cell re-selection, encrypted location update using DCK retrieval, without request for CCK – 2.2.3.6	IOP001-11 2. 2. 3. 6	P
TTR001-11 2. 3.20	AI Signalling Protection Announced cell re-selection with Preferred Neighbour Selected and with Call Restoration, Transmitting encrypted group call, with OTAR of CCK – 2.2.4.1	IOP001-11 2. 2. 4. 1	N/A
TTR001-11 2. 3.20	AI Signalling Protection Announced cell re-selection with Preferred Neighbour Selected and with Call Restoration, Transmitting encrypted group call, without OTAR of CCK – 2.2.4.2	IOP001-11 2. 2. 4. 2	N/A
TTR001-11 2. 6	Signalling Scenarios		
TTR001-11 2. 6. 2	MS-initiated location updating with SCK ciphering, no SCK request, no authentication Registration with encryption applied. Authentication not required by SwMI – 1.1.1	IOP001-11 1. 1. 1	P
TTR001-11 2. 6. 2	MS-initiated location updating with SCK ciphering, no SCK request, no authentication Registration without encryption applied. Authentication not required by SwMI – 1.1.3	IOP001-11 1. 1. 3	-
TTR001-11 2. 6. 3	MS-initiated location updating with SCK ciphering, and authentication Registration with encryption applied. Authentication required by SwMI – 1.1.2	IOP001-11 1. 1. 2	P
TTR001-11 2. 6. 3	MS-initiated location updating with SCK ciphering, and authentication Registration without encryption applied. Authentication required by SwMI – 1.1.4	IOP001-11 1. 1. 4	-
TTR001-11 2. 6. 6	MS-initiated location updating with DCK ciphering, CCK request and authentication Class 3 MS Registration with Class 3 ciphering and CCK request, without encryption applied – 2.1.1	IOP001-11 2. 1. 1	P
TTR001-11 2. 6. 6	MS-initiated location updating with DCK ciphering, CCK request and authentication Class 3 MS Registration with Class 3 ciphering and optional CCK request, with encryption applied – 2.1.2	IOP001-11 2. 1. 2	P
TTR001-11 2. 6. 6	MS-initiated location updating with DCK ciphering, CCK request and authentication Undeclared cell re-selection (without DCK forwarding request) with clear location updating, including request for CCK – 2.2.1.1	IOP001-11 2. 2. 1. 1	P
TTR001-11 2. 6. 6	MS-initiated location updating with DCK ciphering, CCK request and authentication Undeclared cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.1.3	IOP001-11 2. 2. 1. 3	N/A
TTR001-11 2. 6. 6	MS-initiated location updating with DCK ciphering, CCK request and authentication Undeclared cell re-selection, encrypted location update using DCK retrieval, including request for CCK – 2.2.1.5	IOP001-11 2. 2. 1. 5	N/A

Motorola SwMI			Motorola MTH800
TTR001-11 2. 6. 6	MS-initiated location updating with DCK ciphering, CCK request and authentication Unannounced cell re-selection (without DCK forwarding) with clear location updating, including request for CCK – 2.2.2.1	IOP001-11 2. 2. 2. 1	P
TTR001-11 2. 6. 6	MS-initiated location updating with DCK ciphering, CCK request and authentication Unannounced cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.2.3	IOP001-11 2. 2. 2. 3	N/A
TTR001-11 2. 6. 6	MS-initiated location updating with DCK ciphering, CCK request and authentication Unannounced cell re-selection, encrypted location update using DCK retrieval, including request for CCK – 2.2.2.5	IOP001-11 2. 2. 2. 5	N/A
TTR001-11 2. 6. 6	MS-initiated location updating with DCK ciphering, CCK request and authentication Announced type 3 cell re-selection (without DCK forwarding request) with clear location updating, including request for CCK – 2.2.3.1	IOP001-11 2. 2. 3. 1	P
TTR001-11 2. 6. 6	MS-initiated location updating with DCK ciphering, CCK request and authentication Announced type 3 cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.3.3	IOP001-11 2. 2. 3. 3	N//A
TTR001-11 2. 6. 6	MS-initiated location updating with DCK ciphering, CCK request and authentication Announced type 3 cell re-selection, encrypted location update using DCK retrieval, including request for CCK – 2.2.3.5	IOP001-11 2. 2. 3. 5	N/A
TTR001-11 2. 6. 6	MS-initiated location updating with DCK ciphering, CCK request and authentication Announced cell re-selection with Preferred Neighbour Selected and with Call Restoration, Transmitting encrypted group call, without OTAR of CCK – 2.2.4.2	IOP001-11 2. 2. 4. 2	N/A
TTR001-11 2. 6. 7	MS-initiated location updating with DCK ciphering (no CCK request, no authentication) Undeclared cell re-selection (without DCK forwarding request) with clear location updating, without request for CCK – 2.2.1.2	IOP001-11 2. 2. 1. 2	N/A
TTR001-11 2. 6. 7	MS-initiated location updating with DCK ciphering (no CCK request, no authentication) Undeclared cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.1.4	IOP001-11 2. 2. 1. 4	N/A
TTR001-11 2. 6. 7	MS-initiated location updating with DCK ciphering (no CCK request, no authentication) Undeclared cell re-selection, encrypted location update using DCK retrieval, without request for CCK – 2.2.1.6	IOP001-11 2. 2. 1. 6	P
TTR001-11 2. 6. 7	MS-initiated location updating with DCK ciphering (no CCK request, no authentication) Unannounced cell re-selection (without DCK forwarding) with clear location updating, without request for CCK – 2.2.2.2	IOP001-11 2. 2. 2. 2	N/A
TTR001-11 2. 6. 7	MS-initiated location updating with DCK ciphering (no CCK request, no authentication) Unannounced cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.2.4	IOP001-11 2. 2. 2. 4	N/A
TTR001-11 2. 6. 7	MS-initiated location updating with DCK ciphering (no CCK request, no authentication) Unannounced cell re-selection, encrypted location update using DCK retrieval, without request for CCK – 2.2.2.6	IOP001-11 2. 2. 2. 6	P
TTR001-11 2. 6. 7	MS-initiated location updating with DCK ciphering (no CCK request, no authentication) Announced type 3 cell re-selection (without DCK forwarding request) with clear location updating, without request for CCK – 2.2.3.2	IOP001-11 2. 2. 3. 2	N/A
TTR001-11 2. 6. 7	MS-initiated location updating with DCK ciphering (no CCK request, no authentication) Announced type 3 cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.3.4	IOP001-11 2. 2. 3. 4	N//A
TTR001-11 2. 6. 7	MS-initiated location updating with DCK ciphering (no CCK request, no authentication) Announced type 3 cell re-selection, encrypted location update using DCK retrieval, without request for CCK – 2.2.3.6	IOP001-11 2. 2. 3. 6	P

Motorola SwMI			Motorola MTH800
TTR001-11 2. 6. 7	MS-initiated location updating with DCK ciphering (no CCK request, no authentication) Announced cell re-selection with Preferred Neighbour Selected and with Call Restoration, Transmitting encrypted group call, with OTAR of CCK – 2.2.4.1	IOP001-11 2. 2. 4. 1	N/A
TTR001-11 2. 6. 8	MS-initiated location updating with DCK ciphering and authentication Undeclared cell re-selection (without DCK forwarding request) with clear location updating, without request for CCK – 2.2.1.2	IOP001-11 2. 2. 1. 2	N/A
TTR001-11 2. 6. 8	MS-initiated location updating with DCK ciphering and authentication Undeclared cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.1.4	IOP001-11 2. 2. 1. 4	N/A
TTR001-11 2. 6. 8	MS-initiated location updating with DCK ciphering and authentication Undeclared cell re-selection, encrypted location update using DCK retrieval, without request for CCK – 2.2.1.6	IOP001-11 2. 2. 1. 6	N/A
TTR001-11 2. 6. 8	MS-initiated location updating with DCK ciphering and authentication Unannounced cell re-selection (without DCK forwarding) with clear location updating, without request for CCK – 2.2.2.2	IOP001-11 2. 2. 2. 2	N/A
TTR001-11 2. 6. 8	MS-initiated location updating with DCK ciphering and authentication Unannounced cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.2.4	IOP001-11 2. 2. 2. 4	N/A
TTR001-11 2. 6. 8	MS-initiated location updating with DCK ciphering and authentication Unannounced cell re-selection, encrypted location update using DCK retrieval, without request for CCK – 2.2.2.6	IOP001-11 2. 2. 2. 6	N/A
TTR001-11 2. 6. 8	MS-initiated location updating with DCK ciphering and authentication Announced type 3 cell re-selection (without DCK forwarding request) with clear location updating, without request for CCK – 2.2.3.2	IOP001-11 2. 2. 3. 2	N/A
TTR001-11 2. 6. 8	MS-initiated location updating with DCK ciphering and authentication Announced type 3 cell re-selection with DCK forwarding followed by encrypted location update, without request for CCK – 2.2.3.4	IOP001-11 2. 2. 3. 4	N/A
TTR001-11 2. 6. 8	MS-initiated location updating with DCK ciphering and authentication Announced type 3 cell re-selection, encrypted location update using DCK retrieval, without request for DCK – 2.2.3.6	IOP001-11 2. 2. 3. 6	N/A
TTR001-11 2. 6. 8	MS-initiated location updating with DCK ciphering and authentication Announced cell re-selection with Preferred Neighbour Selected and with Call Restoration, Transmitting encrypted group call, with OTAR of CCK – 2.2.4.1	IOP001-11 2. 2. 4. 1	N/A
TTR001-11 2. 6. 9	MS-initiated location updating with DCK ciphering and CCK request Undeclared cell re-selection (without DCK forwarding request) with clear location updating, including request for CCK – 2.2.1.1	IOP001-11 2. 2. 1. 1	N/A
TTR001-11 2. 6. 9	MS-initiated location updating with DCK ciphering and CCK request Undeclared cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.1.3	IOP001-11 2. 2. 1. 3	N/A
TTR001-11 2. 6. 9	MS-initiated location updating with DCK ciphering and CCK request Undeclared cell re-selection, encrypted location update using retrieval, including request for CCK – 2.2.1.5	IOP001-11 2. 2. 1. 5	No
TTR001-11 2. 6. 9	MS-initiated location updating with DCK ciphering and CCK request Unannounced cell re-selection (without DCK forwarding) with clear location updating, including request for CCK – 2.2.2.1	IOP001-11 2. 2. 2. 1	N/A
TTR001-11 2. 6. 9	MS-initiated location updating with DCK ciphering and CCK request Unannounced cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.2.3	IOP001-11 2. 2. 2. 3	N/A
TTR001-11 2. 6. 9	MS-initiated location updating with DCK ciphering and CCK request Unannounced cell re-selection, encrypted location update using DCK retrieval, including request for CCK – 2.2.2.5	IOP001-11 2. 2. 2. 5	No

Motorola SwMI			Motorola MTH800
TTR001-11 2. 6. 9	MS-initiated location updating with DCK ciphering and CCK request Announced type 3 cell re-selection (without DCK forwarding request) with clear location updating, including request for CCK – 2.2.3.1	IOP001-11 2. 2. 3. 1	N/A
TTR001-11 2. 6. 9	MS-initiated location updating with DCK ciphering and CCK request Announced type 3 cell re-selection with DCK forwarding followed by encrypted location update, including request for CCK – 2.2.3.3	IOP001-11 2. 2. 3. 3	N//A
TTR001-11 2. 6. 9	MS-initiated location updating with DCK ciphering and CCK request Announced type 3 cell re-selection, encrypted location update using DCK retrieval, including request for CCK – 2.2.3.5	IOP001-11 2. 2. 3. 5	No
TTR001-11 2. 6. 9	MS-initiated location updating with DCK ciphering and CCK request Announced cell re-selection with Preferred Neighbour Selected and with Call Restoration, Transmitting encrypted group call, without OTAR of CCK – 2.2.4.2	IOP001-11 2. 2. 4. 2	N/A

Note 1 Not tested because the minimum inactivity time is 4 hours.
Comments:

P1 The test case implies radio link failure, therefore the MS cannot send U-
PREPARE. Unannounced cell-reselection was performed according
with TIP clause 10.2.1. (Error in test case).

F1 The test was performed several times. The mobile sometimes
performs PDP context deactivation before receiving explicit information
from SwMI that the advanced link is disconnected.