



IST doc.10

TETRA Terminal Interoperability Certificate

November 2002

NIROS

Manufacturer	Terminal Type	Software/Hardware Release No.	Dates of testing
NIROS	TITAN 4106	SW: 1.51:31a:1 HW: V3 build 3 mod number 30	18-20 November 2002

ISCTI (Istituto Superiore delle Comunicazioni e delle Tecnologie dell'Informazione) has witnessed that the NIROS terminal is operating in accordance with:

TETRA Interoperability Profile:

TIP v2 Core - TTR 001 ver 2.1.1, March 2000
TIP v3 SDS - TTR 001-2 ver 1.0.1, August 2001

The test results for the tested features can be found in the tables of this certificate.

Authorised IOP test engineer

(Ivano Luciani)

Radio Office Manager

(Ing. A. La Padula)

ISCTI has made every effort to ensure that tests have been made correctly, and in accordance with the relevant TIPs. ISCTI has no liability for the test results, or towards the manufacturers.

ISCTI
V.le America 201
00144 Rome, Italy

Tel +39 06 5444 2663
Fax +39 06 5410904

E-mail: Web-

site: <http://www.comunicazioni.it>



Information about the equipment used for testing

Testing during the November 2002 IOP Test Session:

The tests were performed using the following SwMI:

Manufacturer	Infrastructure	Software/Hardware Release No.
Motorola	Dimetra IP R5.0	ZC SW: ZC_APP_ZCTE_R05.00.11.07 NM SW: DMNM-R11.00.09.07 EBTS SW: TSC_PR3_APP-E05.30.63 BRC_APP-E05.20.50

ISCTI has made every effort to ensure that tests have been made correctly, and in accordance with the relevant TIPs. ISCTI has no liability for the test results, or towards the manufacturers.

ISCTI
V.le America 201
00144 Rome, Italy

Tif. +39 06 5444 2663
Fax +39 06 5410904

E-mail: Web- site: <http://www.comunicazioni.it>



Additional information about the test performed

The tests were performed in the 380-400 MHz band. The SwMI was operating with the following configuration:

MCC	238
MNC	01
Colour code	41
LA20 carrier frequency (BS Tx)	393.6125 MHz
LA21 carrier frequency (BS Tx)	393.5375 MHz
LA30 carrier frequency (BS Tx)	421.075 MHz
LA31 carrier frequency (BS Tx)	421.175 MHz
PSTN gateway	43488011
Subscriber classes	FFFF ₁₆

Test Results

The test results are shown in the tables below.

Test results and the certificates from previous IOP test session are available on TETRA MoU web site (<http://www.tetramou.com/interoperability>).

Tables indicate whether or not tests addressing a specific requirement of the TIP specification have been performed, whether or not the requirement is applicable for the SwMI, and the result of the test if executed. Each entry of the table may take one of seven values:

- : No test performed.
- N/A: Not applicable for the SwMI
- NTPA: No Test Plan Available
- P : Pass
- No : Not supported by Terminal
- F : Fail
- I : Inconclusive

No test performed (-) is assigned in case of no test case performed during the IOP test session. The test results have been derived from examining the behaviour of a live system. The verdicts indicated are based on the log evaluation of the information exchange between the SwMI and the terminal indicated in the following tables. The verdicts reflect the fact that at the time of the IOP testing it was/was not possible to demonstrate a behaviour that was in accordance with the related requirement.

ISCTI has made every effort to ensure that tests have been made correctly, and in accordance with the relevant TIPs. ISCTI has no liability for the test results, or towards the manufacturers.

ISCTI
V.le America 201
00144 Rome, Italy

Tif. +39 06 5444 2663
Fax +39 06 5410904

E-mail: Web- site: <http://www.comunicazioni.it>



Table 1: Test performed CORE TIP V2

Motorola SwMI	TITAN4106
6 Registration	
6.1 ITSI attach	P
6.2 ITSI attach including group attachment	P
6.3 Roaming location updating	-
6.4 De-registration	P
7 Individual call	
7.1 Call setup	
7.1.1 Hook signalling Semi-duplex	-
7.1.1 Hook signalling Semi-duplex, Queuing	-
7.1.1 Hook signalling Duplex	N/A
7.1.2 Direct through-connect Semi-duplex	N/A
7.1.2 Direct through-connect Semi-duplex, queuing	N/A
7.1.2 Direct through-connect Duplex	N/A
7.1.3 Call setup Modifications	
7.1.3.1.1 By SwMI, Direct to Hook	P
7.1.3.1.2 By SwMI, Hook to Direct	N/A
7.1.3.2 By called Party (7.1.3.2.3 Core 3)	N/A
7.2 Transmission control	
7.2.1 End of transmission, Hook signalling	P
7.2.1 End of transmission, Direct call	N/A
7.2.2 Request to transmit, Hook signalling	P
7.2.2 Request to transmit, Direct call	N/A
7.2.3 Request for speech item, Hook signalling	P
7.2.3 Pre emptive speech item request	P
7.3 Call maintenance	N/A
7.4 Call disconnection (by calling party- simplex)	P
7.4 Call disconnection (by calling party - duplex)	N/A
7.5 Emergency individual call	N/A
7.5.1 Emergency speech item request	N/A
7.5.2 Emergency individual call modification	N/A
8 Group management	
8.4 MS Attachment of the selected group	P
8.4 MS Attachment of the selected group (Rejection)	P
8.4 MS Attachment of the Null group	P
8.4 MS Change of the selected group	P
8.5 Multiple group attachment	-
8.5 Multiple group attachment, failure	N/A
8.6 MS initiated detachment	P
8.7 SwMI initiated group attachment and detachment	

ISCTI has made every effort to ensure that tests have been made correctly, and in accordance with the relevant TIPs. ISCTI has no liability for the test results, or towards the manufacturers.

ISCTI
V.le America 201
00144 Rome, Italy

Tif. +39 06 5444 2663
Fax +39 06 5410904

E-mail: Web- site: <http://www.comunicazioni.it>



Motorola SwMI	TITAN4106
8.7.1 SwMI initiated detachment (5.4.1)	N/A
8.7.2 SwMI initiated attachment (5.4.1)	N/A
8.7.3 SwMI initiated group reporting	N/A
8.7.4 SwMI initiated registration with group report request	N/A
8.7.5 SwMI initiated registration without group report request	NTPA
9 Group call	
9.1 Call setup	P
9.1 Call setup (Queuing)	P
9.1.1 Call setup modifications, Point-to-multipoint to point to point	N/A
9.1.1 Call setup modifications, Call priority	NTPA
9.2.1 End of transmission	P
9.2.2 Request to transmit	P
9.2.3 Pre-emptive speech item request	P
9.3 Call disconnection	P
9.4 Late entry	P
9.5 Emergency group call .	
9.5 Emergency group call (Setup to busy group)	-
9.5.1 Emergency resource pre-emption	-
9.5.2 Emergency group call modification	N/A
10 Cell re-selection	
10.1 Undeclared cell re-selection	-
10.2 Unannounced cell re-selection with call restoration	
10.2.1 (Group call)	-
10.2.1 (Queuing, group call)	-
10.2.1 (individual call)	-
10.2.1 (Queuing, individual call)	-
10.2.2 Announced cell re-selection without preferred Neighbour selected with call restoration	
10.2.2 (Group call)	-
10.2.2 (Queuing, group call)	-
10.2.2 (Pre-emption, group call)	-
10.2.2 (individual call, traffic) TX	-
10.2.2 (individual call, traffic) Rx	-
10.2.2 (individual call, inactivity)	-
10.2.2 (Queuing, individual call, traffic) Tx	-
10.2.2 (Queuing, individual call, traffic) RX	-
10.2.2 (Queuing, individual call, inactivity)	-
11 Short data service	
11.1 Status messages MS to dispatcher)	P
11.1 Status messages MS to MS	N/A
11.1 Status messages (Text messaging)	-

ISCTI has made every effort to ensure that tests have been made correctly, and in accordance with the relevant TIPs. ISCTI has no liability for the test results, or towards the manufacturers.

ISCTI
V.le America 201
00144 Rome, Italy

Tlf. +39 06 5444 2663
Fax +39 06 5410904

E-mail: Web- site: <http://www.comunicazioni.it>



Motorola SwMI	TITAN4106
12 Telephone call	
12.2 Call Set-up	
12.2.1 MS Originated, Late Through-Connect	P
12.2.2 MS Originated, Early Through-Connect	N/A
12.2.3 MS Originated, Call Queued	P
12.2.4 MS Terminated	P
12.3 Call Maintenance	NTPA
12.4 DTMF Over-dial	P
12.5 Disconnect Causes	P
12.6 Emergency telephone call	NTPA

Table 2: Test performed SDS TIP V3

Motorola SwMI	TITAN4106
7 User defined data type 1, 2 and 3	
7 Type 1	N/A
7 Type 2	N/A
7 Type 3	N/A
8 User defined data type 4	
8 User defined data type 4 without SDS-TL	N/A
8.1.2 MS to MS, Standard Report	P
8.1.2 MS to MS, Standard Report with Store and Forward	N/A
8.1.3 MS to MS, Short Report	N/A
8.2 Text messaging	
8.2.1.4 No acknowledgement requested	N/A
8.2.2 MS to MS, Short report	N/A

ISCTI has made every effort to ensure that tests have been made correctly, and in accordance with the relevant TIPs. ISCTI has no liability for the test results, or towards the manufacturers.

ISCTI
V.le America 201
00144 Rome, Italy

Tif. +39 06 5444 2663
Fax +39 06 5410904

E-mail: Web-site: <http://www.comunicazioni.it>



Comments:

No comment

ISCTI has made every effort to ensure that tests have been made correctly, and in accordance with the relevant TlPs.
ISCTI has no liability for the test results, or towards the manufacturers.

ISCTI
V.le America 201
00144 Rome, Italy

Tlf. +39 06 5444 2663
Fax +39 06 5410904

E-mail: Web- site: <http://www.comunicazioni.it>